

ARTO 2 LED 2600LM RCR I CL. IP20 592X592X45MM 830 26W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|---|
| Ingress protection: | IP20 |
| Rated power of the luminaire [W]*: | 26 |
| Luminous flux [lm]*: | 2600 |
| Colour temperature [K]: | 3000 |
| Color rendering index (Ra) >: | 80 |
| SDCM: | 3 |
| Material of the body: | powder coated steel |
| Diffuser material: | PS |
| Diffuser type: | OPAL |
| Mounting version: | surface mounted; recessed mounted in modular ceiling possible |

CHARACTERISTICS

Surface-mounted modular ceiling luminaire with integrated energy-efficient LED panel made of white powder-coated steel. Opalized polystyrene diffuser ensures uniform light distribution. The central part of the luminaire is a louver, which is a part of a modular ceiling. Thanks to it the luminaire perfectly fits into the interior decor.

APPLICATION

Multifunctional luminaire designed for surface mounting with the possibility of flush installation in modular ceilings in office, representative, or general utility rooms. It is also used as the main source of light. Luminaire is perfect for new applications as well as for replacing traditional fluorescent fixtures with energy-saving LED solutions.

ARTO 2 LED 2600LM RCR I CL. IP20 592X592X45MM 830 26W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------------|-----------------------------------|---|
| Index: | 021213 | Mounting dimensions [mm]: | 362 |
| Light source: | LED module | Ingress protection: | IP20 |
| Nominal power [W]: | 25 | Mounting version: | surface mounted; recessed mounted in modular ceiling possible |
| Rated power of the luminaire [W]: | 26 | Working temperature [°C]: | 35 |
| Supply voltage [V]: | 220 - 240 | Motion sensor: | yes |
| Frequency [Hz]: | 50 - 60 | Dimensions (H/W/T/S) [mm]: | 592/592/45 |
| Luminous flux [lm]: | 2600 | Net weight [kg]: | 5.100 |
| Luminous efficacy [lm/W]: | 100 | Warranty [years]: | 5 |
| Electrical protection class: | I | Category type: | troffers |
| Colour temperature [K]: | 3000 | AC voltage range [V]: | 198 - 264 |
| Color rendering index (Ra) >: | 80 | LED lifespan L70B50 [h]: | 116000 |
| SDCM: | 3 | LED lifespan L80B10 [h]: | 73000 |
| Power factor: | 0.95 | LED lifespan L90B10 [h]: | 36000 |
| Surge protection [kV]: | 2 | Light distribution type: | lamertian |
| Diffuser material: | PS | Warranty [years]: | 5 |
| Diffuser type: | OPAL | CE certificate: | 253/2023 |
| Diffuser colour: | white | Manual: | Download PDF |
| Material of the body: | powder coated steel | Plik LDT: | Download |
| Colour of the body: | white | | |

ARTO 2 LED 2600LM RCR I CL. IP20 592X592X45MM 830 26W

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|--|
| 374845 | Frame adapter KG 635x635 WHITE |
| 998966 | Frame steel white structure RAL9016 600x600 SM "well effect" |
| 998973 | Frame steel white gloss RAL9016 600x600 SM "well effect" |



Frame adapter KG 635x635
WHITE (374845)



Frame steel white structure RAL9016
600x600 SM "well effect" (998966)



Frame steel white gloss RAL9016
600x600 SM "well effect" (998973)

Card creation date: 13 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 253/2023