ARTO 2 LED 2600LM RCR I CL. IP20 592X592X45MM 830 26W

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Rated power of the luminaire [W]*:	26
Luminous flux [lm]*:	2600
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Material of the body:	powder coated steel
Diffuser material:	PS
Diffuser type:	OPAL
Mounting version:	surface mounted; recessed mounted in modular ceiling possible

CHARACTERISTICS

Surface-mounted modular ceiling luminaire with integrated energy-efficient LED panel made of white powder-coated steel. Opalized polystyrene diffuser ensures uniform light distribution. The central part of the luminaire is a louver, which is a part of a modular ceiling. Thanks to it the luminaire perfectly fits into the interior decor.

APPLICATION

Multifunctional luminaire designed for surface mounting with the possibility of flush installation in modular ceilings in office, representative, or general utility rooms. It is also used as the main source of light. Luminaire is perfect for new applications as well as for replacing traditional fluorescent fixtures with energy-saving LED solutions.

ARTO 2 LED 2600LM RCR I CL. IP20 592X592X45MM 830 26W

DETAILED CARD

TECHNICAL PARAMETERS TABLE


Index:	021213	**Mounting dimensions [mm]:**	362
Light source:	LED module	**Ingress protection:**	IP20
Nominal power [W]:	25	**Mounting version:**	surface mounted; recessed mounted in modular ceiling possible
Rated power of the luminaire [W]:	26		
Supply voltage [V]:	220 - 240	**Working temperature [°C]:**	from 0 to +35
Frequency [Hz]:	50 - 60	**Motion sensor:**	yes
Luminous flux [lm]:	2600	**Dimensions (H/W/T/S) [mm]:**	592/592/45
Luminous efficacy [lm/W]:	100	**Net weight [kg]:**	5.100
Electrical protection class:	I	**Warranty [years]:**	5
Colour temperature [K]:	3000	**Category type:**	troffers
Color rendering index (Ra) >:	80	**AC voltage range [V]:**	198 - 264
SDCM:	3	**LED lifespan L70B50 [h]:**	116000
Power factor:	0.95	**LED lifespan L80B10 [h]:**	73000
Surge protection [kV]:	2	**LED lifespan L90B10 [h]:**	36000
Diffuser material:	PS	**Light distribution type:**	lambertian
Diffuser type:	OPAL	**Warranty [years]:**	5
Diffuser colour:	white	**CE certificate:**	253/2023
Material of the body:	powder coated steel	**Manual:**	Download PDF
Colour of the body:	white	**Plik LDT:**	Download

ARTO 2 LED 2600LM RCR I CL. IP20 592X592X45MM 830 26W


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
374845	Frame adapter KG 635x635 WHITE
998973	Frame steel white gloss RAL9016 600x600 SM "well effect"



Frame adapter KG 635x635 WHITE (374845)



Frame steel white gloss RAL9016 600x600 SM "well effect" (998973)

Card creation date: 13 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 253/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl