

ARTO 2 LED 3380LM I CL. IP20 592X592X45MM 840 31W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|---|
| Ingress protection: | IP20 |
| Rated power of the luminaire [W]*: | 31 |
| Luminous flux [lm]*: | 3380 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Material of the body: | powder coated steel |
| Diffuser material: | PS |
| Diffuser type: | OPAL |
| Mounting version: | surface mounted; recessed mounted in modular ceiling possible |

CHARACTERISTICS

Surface-mounted modular ceiling luminaire with integrated energy-efficient LED panel made of white powder-coated steel. Opalized polystyrene diffuser ensures uniform light distribution. The central part of the luminaire is a louvre, which is a part of a modular ceiling. Thanks to it the luminaire perfectly fits into the interior decor.

APPLICATION

Multifunctional luminaire designed for surface mounting with the possibility of flush installation in modular ceilings in office, representative, or general utility rooms. It is also used as the main source of light. Luminaire is perfect for new applications as well as for replacing traditional fluorescent fixtures with energy-saving LED solutions.

ARTO 2 LED 3380LM I CL. IP20 592X592X45MM 840 31W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------------|-----------------------------------|---|
| Index: | 021022 | Mounting dimensions [mm]: | 362 |
| Rated power of the luminaire [W]: | 31 | Ingress protection: | IP20 |
| Light source: | LED module | Mounting version: | surface mounted; recessed mounted in modular ceiling possible |
| Colour temperature [K]: | 4000 | Working temperature [°C]: | 35 |
| Nominal power [W]: | 30 | Dimensions (H/W/T/S) [mm]: | 592/592/45 |
| Luminous flux [lm]: | 3380 | Net weight [kg]: | 4.900 |
| Supply voltage [V]: | 220 - 240 | Warranty [years]: | 5 |
| Frequency [Hz]: | 50 - 60 | Category type: | louvres |
| Luminous efficacy [lm/W]: | 110 | AC voltage range [V]: | 198 - 264 |
| Electrical protection class: | I | LED lifespan L70B50 [h]: | 116000 |
| Colour rendering index: | >80 | LED lifespan L80B20 [h]: | 73000 |
| SDCM: | ≤ 3 | LED lifespan L90B10 [h]: | 36000 |
| Power factor: | 0.95 | Light distribution type: | lambertian |
| Surge protection [kV]: | 2 | Warranty [years]: | 5 |
| Diffuser material: | PS | CE certificate: | 253/2023 |
| Diffuser type: | OPAL | Manual: | Download PDF |
| Diffuser colour: | white | | |
| Material of the body: | powder coated steel | | |
| Colour of the body: | white | | |

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 253/2023