

# SIZZANO MULTI Z 600MM 2100-3600LM 830 IP40 I CL. 21-37W BLACK RING

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Rated power [W] - range:</b>	21-37
<b>Luminous flux of the luminaire [lm] - range:</b>	2100 - 3600
<b>Colour temperature [K]:</b>	3000
<b>Diffuser material:</b>	PMMA
<b>Diffuser type:</b>	OPAL
<b>Ring material:</b>	HIPS
<b>Dimensions (H/W/T/S) [mm]:</b>	630/50

## CHARACTERISTICS

Sizzano is a suspended ring-shaped LED luminaire, whose shape and final form is given by an impact-resistant diffuser made by rotomoulding. The design is complemented by an inner collar in black or any RAL color to match the character and color scheme of the room.

## APPLICATION

The captivating proportions of Sizzano will emphasize the prestigious character of any room without the effect of tactless domination. The length of the pendant can be adjusted to individual needs and the desired final effect. The complete adjustable suspension system with the central box is supplied with the luminaire. Multi LED versions allow the selection of 4 luminaire power and flux settings, increasing the versatility and functionality of the luminaire and reducing the number of indexes to the minimum.


# SIZZANO MULTI Z 600MM 2100-3600LM 830 IP40 I CL. 21-37W BLACK RING

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	468063	<b>Diffuser material:</b>	PMMA
<b>EAN:</b>	5905963468063	<b>Diffuser type:</b>	OPAL
<b>Light source:</b>	LED module	<b>Diffuser colour:</b>	white
<b>Rated power [W] - range:</b>	21-37	<b>Ring material:</b>	HIPS
<b>Luminous flux of the luminaire [lm] - range:</b>	2100 - 3600	<b>Ring colour:</b>	black
<b>Colour temperature [K]:</b>	3000	<b>Dimensions (H/W/T/S) [mm]:</b>	630/50
<b>Supply voltage [V]:</b>	220 - 240	<b>Ingress protection:</b>	IP40
<b>Frequency [Hz]:</b>	50 - 60	<b>Mounting version:</b>	suspended
<b>Luminous efficacy [lm/W]:</b>	98	<b>Net weight [kg]:</b>	2.800
<b>Energy efficiency class:</b>	E	<b>Warranty [years]:</b>	5
<b>Electrical protection class:</b>	I	<b>CE certificate:</b>	<a href="#">216/2023</a>
<b>Colour rendering index:</b>	>80	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>SDCM:</b>	≤ 3	<b>Plik LDT:</b>	<a href="#">Download</a>
<b>LED lifespan L80B20 [h]:</b>	70000		

## LIGHT CURVES



Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 216/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl