

SIZZANO MULTI Z 1000MM 3200-5600LM 840 IP40 I CL. 32-55W BLACK RING

DETAILED CARD



TECHNICAL PARAMETERS

Rated power [W] - range:	32-55
Luminous flux of the luminaire [lm] - range:	3200 - 5600
Colour temperature [K]:	4000
Diffuser material:	PMMA
Diffuser type:	OPAL
Ring material:	HIPS
Dimensions (H/W/T/S) [mm]:	970/80

CHARACTERISTICS

Sizzano is a suspended ring-shaped LED luminaire, whose shape and final form is given by an impact-resistant diffuser made by rotomoulding. The design is complemented by an inner collar in black or any RAL color to match the character and color scheme of the room.

APPLICATION

The captivating proportions of Sizzano will emphasize the prestigious character of any room without the effect of tactless domination. The length of the pendant can be adjusted to individual needs and the desired final effect. The complete adjustable suspension system with the central box is supplied with the luminaire. Multi LED versions allow the selection of 4 luminaire power and flux settings, increasing the versatility and functionality of the luminaire and reducing the number of indexes to the minimum.


SIZZANO MULTI Z 1000MM 3200-5600LM 840 IP40 I CL. 32-55W BLACK RING

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	468032	Diffuser material:	PMMA
EAN:	5905963468032	Diffuser type:	OPAL
Light source:	LED module	Diffuser colour:	white
Rated power [W] - range:	32-55	Ring material:	HIPS
Luminous flux of the luminaire [lm] - range:	3200 - 5600	Ring colour:	black
Colour temperature [K]:	4000	Dimensions (H/W/T/S) [mm]:	970/80
Supply voltage [V]:	220 - 240	Ingress protection:	IP40
Frequency [Hz]:	50 - 60	Mounting version:	suspended
Luminous efficacy [lm/W]:	103	Number on the palette [pcs]:	1
Energy efficiency class:	E	Net weight [kg]:	6,800
Electrical protection class:	I	Warranty [years]:	5
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	216/2023
LED lifespan L70B50 [h]:	112000	Manual:	Download PDF
LED lifespan L80B20 [h]:	70000	Plik LDT:	Download
LED lifespan L90B10 [h]:	34000		

LIGHT CURVES



Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 216/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl