SIZZANO MULTI Z 600MM 2200-3800LM 840 IP40 I CL. 21-37W BLACK RING

DETAILED CARD



TECHNICAL PARAMETERS

Rated power [W] - range:	21-37
Luminous flux of the luminaire [lm] - range:	2200 - 3800
Colour temperature [K]:	4000
Diffuser material:	PMMA
Diffuser type:	OPAL
Diffuser colour:	white
Ring material:	HIPS
Dimensions (H/W/T/S) [mm]:	630/50

CHARACTERISTICS

Sizzano is a suspended ring-shaped LED luminaire, whose shape and final form is given by an impact-resistant diffuser made by rotomoulding. The design is complemented by an inner collar in black or any RAL color to match the character and color scheme of the room.

APPLICATION

The captivating proportions of Sizzano will emphasize the prestigious character of any room without the effect of tactless domination. The length of the pendant can be adjusted to individual needs and the desired final effect. The complete adjustable suspension system with the central box is supplied with the luminaire. Multi LED versions allow the selection of 4 luminaire power and flux settings, increasing the versatility and functionality of the luminaire and reducing the number of indexes to the minimum.

SIZZANO MULTI Z 600MM 2200-3800LM 840 IP40 I CL. 21-37W BLACK RING

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	468001
EAN:	5905963468001
Light source:	LED module
Rated power [W] - range:	21-37
Luminous flux of the luminaire [lm] - range:	2200 - 3800
Colour temperature [K]:	4000
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	103
Energy efficiency class:	E
Electrical protection class:	I
Color rendering index (Ra) >:	80
SDCM:	3
LED lifespan L70B50 [h]:	112000
LED lifespan L80B10 [h]:	70000
LED lifespan L90B10 [h]:	34000
Working temperature [°C]:	from 0 to +35

Diffuser material:	PMMA
Diffuser type:	OPAL
Diffuser colour:	white
Ring material:	HIPS
Ring colour:	black
Dimensions (H/W/T/S) [mm]:	630/50
Ingress protection:	IP40
Mounting version:	suspended
Cable length [m]:	1.20
Number on the palette [pcs]:	4
Net weight [kg]:	2.800
Warranty [years]:	5
CE certificate:	216/2023
Manual:	Download PDF
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Plik LDT:	Download

Card creation date: 24 July 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 216/2023

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl