

SIZZANO Z 1000MM 4200LM 840 IP40 I CL. DALI 40W BLACK RING

DETAILED CARD



TECHNICAL PARAMETERS

Rated power [W] - range:	40
Luminous flux of the luminaire [lm] - range:	4200
Colour temperature [K]:	4000
Diffuser material:	PMMA
Diffuser type:	OPAL
Ring material:	HIPS
Dimensions (H/W/T/S) [mm]:	970/80

CHARACTERISTICS

Sizzano is a suspended ring-shaped LED luminaire, whose shape and final form is given by an impact-resistant diffuser made by rotomoulding. The design is complemented by an inner collar in black or any RAL color to match the character and color scheme of the room.

APPLICATION

The captivating proportions of Sizzano will emphasize the prestigious character of any room without the effect of tactless domination. The length of the pendant can be adjusted to individual needs and the desired final effect. The complete adjustable suspension system with the central box is supplied with the luminaire.

SIZZANO Z 1000MM 4200LM 840 IP40 I CL. DALI 40W BLACK RING

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	468049	Diffuser material:	PMMA
EAN:	5905963468049	Diffuser type:	OPAL
Light source:	LED module	Diffuser colour:	white
Rated power [W] - range:	40	Ring material:	HIPS
Luminous flux of the luminaire [lm] - range:	4200	Ring colour:	black
Colour temperature [K]:	4000	Dimensions (H/W/T/S) [mm]:	970/80
Supply voltage [V]:	220 - 240	Ingress protection:	IP40
Frequency [Hz]:	50 - 60	Mounting version:	suspended
Luminous efficacy [lm/W]:	105	DIMM DALI:	yes
Energy efficiency class:	E	Number on the palette [pcs]:	1
Electrical protection class:	I	Net weight [kg]:	7.100
Color rendering index (Ra) >:	80	Warranty [years]:	5
SDCM:	3	Warranty [years]:	5
LED lifespan L70B50 [h]:	112000	CE certificate:	216/2023
LED lifespan L80B10 [h]:	70000	Manual:	Download PDF
LED lifespan L90B10 [h]:	34000	Plik LDT:	Download

Card creation date: 14 November 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 216/2023