## SIZZANO Z 1000MM 4200LM 840 IP40 I CL. DALI 40W BLACK RING

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

| Rated power [W] - range:                     | 40     |
|--|--------|
| Luminous flux of the luminaire [lm] - range: | 4200   |
| Colour temperature [K]:                      | 4000   |
| Diffuser material:                           | PMMA   |
| Diffuser type:                               | OPAL   |
| Ring material:                               | HIPS   |
| Dimensions (H/W/T/S) [mm]:                   | 970/80 |

## **CHARACTERISTICS**

Sizzano is a suspended ring-shaped LED luminaire, whose shape and final form is given by an impact-resistant diffuser made by rotomoulding. The design is complemented by an inner collar in black or any RAL color to match the character and color scheme of the room.

## **APPLICATION**

The captivating proportions of Sizzano will emphasize the prestigious character of any room without the effect of tactless domination. The length of the pendant can be adjusted to individual needs and the desired final effect. The complete adjustable suspension system with the central box is supplied with the luminaire.



# SIZZANO Z 1000MM 4200LM 840 IP40 I CL. DALI 40W BLACK RING

**DETAILED CARD** 

## **TECHNICAL PARAMETERS TABLE**

| Index:                                       | 468049        |
|--|---------------|
|  |               |
| EAN:   | 5905963468049 |
| Light source:                                | LED module    |
| Rated power [W] - range:                     | 40            |
| Luminous flux of the luminaire [lm] - range: | 4200          |
| Colour temperature [K]:                      | 4000          |
| Supply voltage [V]:                          | 220 - 240     |
| Frequency [Hz]:                              | 50 - 60       |
| Luminous efficacy [lm/W]:                    | 105           |
| Energy efficiency class:                     | Е             |
| Electrical protection class:                 | 1             |
| Colour rendering index:                      | 80            |
| SDCM:  | ≤3            |
| LED lifespan L70B50 [h]:                     | 112000        |
| LED lifespan L80B20 [h]:                     | 70000         |
| LED lifespan L90B10 [h]:                     | 34000         |

| Diffuser material:           | PMMA         |
|------------------------------|--------------|
| Diffuser type:               | OPAL         |
| Diffuser colour:             | white        |
| Ring material:               | HIPS         |
| Ring colour:                 | black        |
| Dimensions (H/W/T/S) [mm]:   | 970/80       |
| Ingress protection:          | IP40         |
| Mounting version:            | suspended    |
| DIMM DALI:                   | yes          |
| Number on the palette [pcs]: | 1            |
| Net weight [kg]:             | 7.100        |
| Warranty [years]:            | 5            |
| Warranty [years]:            | 5            |
| CE certificate:              | 216/2023     |
| Manual:                      | Download PDF |
| Plik LDT:                    | Download     |

Card creation date: 02 January 2025



