

SIZZANO Z 1000MM 4200LM 840 IP40 I CL. DALI 40W BLACK RING

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|--------|
| Rated power [W] - range: | 40 |
| Luminous flux of the luminaire [lm] - range: | 4200 |
| Colour temperature [K]: | 4000 |
| Diffuser material: | PMMA |
| Diffuser type: | OPAL |
| Ring material: | HIPS |
| Dimensions (H/W/T/S) [mm]: | 970/80 |

CHARACTERISTICS

Sizzano is a suspended ring-shaped LED luminaire, whose shape and final form is given by an impact-resistant diffuser made by rotomoulding. The design is complemented by an inner collar in black or any RAL color to match the character and color scheme of the room.

APPLICATION

The captivating proportions of Sizzano will emphasize the prestigious character of any room without the effect of tactless domination. The length of the pendant can be adjusted to individual needs and the desired final effect. The complete adjustable suspension system with the central box is supplied with the luminaire.

SIZZANO Z 1000MM 4200LM 840 IP40 I CL. DALI 40W BLACK RING

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------|------------------------------|------------------------------|
| Index: | 468049 | Diffuser material: | PMMA |
| EAN: | 5905963468049 | Diffuser type: | OPAL |
| Light source: | LED module | Diffuser colour: | white |
| Rated power [W] - range: | 40 | DIMM DALI: | yes |
| Luminous flux of the luminaire [lm] - range: | 4200 | Ring material: | HIPS |
| Colour temperature [K]: | 4000 | Ring colour: | black |
| Supply voltage [V]: | 220 - 240 | Dimensions (H/W/T/S) [mm]: | 970/80 |
| Frequency [Hz]: | 50 - 60 | Ingress protection: | IP40 |
| Luminous efficacy [lm/W]: | 105 | Mounting version: | suspended |
| Energy efficiency class: | E | Number on the palette [pcs]: | 1 |
| Electrical protection class: | I | Net weight [kg]: | 7.100 |
| Colour rendering index: | >80 | Warranty [years]: | 5 |
| SDCM: | ≤ 3 | Warranty [years]: | 5 |
| LED lifespan L70B50 [h]: | 112000 | CE certificate: | 216/2023 |
| LED lifespan L80B20 [h]: | 70000 | Manual: | Download PDF |
| LED lifespan L90B10 [h]: | 34000 | Plik LDT: | |

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 216/2023