SIZZANO Z 1000MM 5600LM 840 IP40 I CL. DALI 55W BLACK RING

DETAILED CARD





TECHNICAL PARAMETERS

Rated power [W] - range:	55
Luminous flux of the luminaire [lm] - range:	5600
Colour temperature [K]:	4000
Diffuser material:	PMMA
Diffuser type:	OPAL
Ring material:	HIPS
Dimensions (H/W/T/S) [mm]:	970/80

CHARACTERISTICS

Sizzano is a suspended ring-shaped LED luminaire, whose shape and final form is given by an impact-resistant diffuser made by rotomoulding. The design is complemented by an inner collar in black or any RAL color to match the character and color scheme of the room.

APPLICATION

The captivating proportions of Sizzano will emphasize the prestigious character of any room without the effect of tactless domination. The length of the pendant can be adjusted to individual needs and the desired final effect. The complete adjustable suspension system with the central box is supplied with the luminaire.



SIZZANO Z 1000MM 5600LM 840 IP40 I CL. DALI 55W BLACK RING

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	468056
EAN:	5905963468056
Light source:	LED module
Rated power [W] - range:	55
Luminous flux of the luminaire [lm] - range:	5600
Colour temperature [K]:	4000
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	102
Energy efficiency class:	E
Electrical protection class:	1
Colour rendering index:	80
SDCM:	≤3
LED lifespan L70B50 [h]:	112000
LED lifespan L80B20 [h]:	70000
LED lifespan L90B10 [h]:	34000

Diffuser material:	PMMA
Diffuser type:	OPAL
Diffuser colour:	white
Ring material:	HIPS
Ring colour:	black
Dimensions (H/W/T/S) [mm]:	970/80
Ingress protection:	IP40
Mounting version:	suspended
DIMM DALI:	yes
Number on the palette [pcs]:	1
Net weight [kg]:	7.100
Warranty [years]:	5
Warranty [years]:	5
CE certificate:	<u>216/2023</u>
Manual:	Download PDF
Plik LDT:	<u>Download</u>

Card creation date: 02 January 2025



