

# BARIS 52 LED N 583MM 900LM 840 IP44 I CL. PRM ANODA CO 9W SINGLE

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP44
<b>Impact resistance:</b>	IK03
<b>Rated power of the luminaire [W]*:</b>	9
<b>Luminous flux [lm]*:</b>	900
<b>Colour temperature [K]:</b>	4000
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	PRM
<b>Mounting version:</b>	surface

## CHARACTERISTICS

Suspended or surface-mounted luminaire with classic proportions and modern design. The housing of the luminaire is made of an anodized aluminum profile in gray or an aluminum profile painted in white or black (other colors available on request). The optical system is in the form of a prismatic diffuser (PRM); a dedicated, flexible opal diffuser evenly illuminating the luminaire or with a louvre that meets the stringent glare requirements UGR <19 covered with a transparent cover. The modularity and dismantling of the luminaire allow for the replacement of electronic components, such as the LED strip, power supply, and replacement of the lampshade by qualified persons. The luminaire profile has been adapted to work with intelligent IoT modules, which will additionally optimize the level and amount of light provided by it, as well as the direct/indirect version that allows some of the light to be directed upwards, illuminating the ceiling. The luminaire is equipped with a unique suspension system that facilitates the installation of the luminaire and adjustment of the suspension. All Baris 52 LED Single suspended luminaires include 1.2m long pendants with a socket in the set and are equipped with a diffuser.

## APPLICATION

The luminaire is intended for indoor use. It is used as the main light source and favors office work that requires concentrated vision. The unique design, the energy-saving LED modules, and the ability to work with external lighting control systems in the DALI standard predestine the luminaire for use in modern office buildings of class A+, with a particular focus on offices, prestigious rooms, conference rooms, passageways, and wherever IP44 protection is required. Baris 52 LED Single is, as the name suggests, a single lighting element with a specific length. To create a line of length up to 6 meters without connecting the profile and up to 25 meters without connecting the lampshade, version BARIS 52 LED.

# BARIS 52 LED N 583MM 900LM 840 IP44 I CL. PRM ANODA CO 9W SINGLE

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	461750	Diffuser material:	PC
Rated power of the luminaire [W]:	9	Colour of the body:	grey
EAN:	5905963461750	Diffuser colour:	clear
Colour temperature [K]:	4000	Dimensions (H/W/T/S) [mm]:	583/69/52
Light source:	LED module	Optics:	Microprism
Luminous flux [lm]:	900	Material of the body:	aluminium
Diffuser type:	PRM	Mounting version:	surface
Supply voltage [V]:	220 - 240	Impact resistance:	IK03
Frequency [Hz]:	50 - 60	Ingress protection:	IP44
Luminous efficacy [lm/W]:	89	Working temperature [°C]:	from -25 to +35
Energy efficiency class:	F	Net weight [kg]:	1
Electrical protection class:	I	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	<a href="#">233/2023</a>
LED lifespan L70B50 [h]:	111500	ENEC Certificate:	<a href="#">PL BBJ/006/2022/M1</a>
LED lifespan L80B20 [h]:	70400	PZH certificate:	<a href="#">B-BK-60112-0357/2023</a>
LED lifespan L90B10 [h]:	34000	Manual:	<a href="#">Download PDF</a>
		Plik LDT:	<a href="#">Pobierz</a>

Card creation date: 11 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 233/2023