


BARIS 52 LED Z 2263MM 3550LM 830 IP44 I CL. PRM ANODA CO 32W SINGLE

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|-----------|
| Ingress protection: | IP44 |
| Impact resistance: | IK06 |
| Rated power of the luminaire [W]*: | 32 |
| Luminous flux [lm]*: | 3550 |
| Colour temperature [K]: | 3000 |
| Material of the body: | aluminium |
| Colour of the body: | grey |
| Diffuser material: | PC |
| Diffuser type: | PRM |
| Mounting version: | suspended |

CHARACTERISTICS

Suspended or surface-mounted luminaire with classic proportions and modern design. The housing of the luminaire is made of an anodized aluminum profile in gray or an aluminum profile painted in white or black (other colors available on request). The optical system is in the form of a prismatic diffuser (PRM); a dedicated, flexible opal diffuser evenly illuminating the luminaire or with a louver that meets the stringent glare requirements UGR <19 covered with a transparent cover. The modularity and dismantling of the luminaire allow for the replacement of electronic components, such as the LED strip, power supply, and replacement of the lampshade by qualified persons. The luminaire profile has been adapted to work with intelligent IoT modules, which will additionally optimize the level and amount of light provided by it, as well as the direct/indirect version that allows some of the light to be directed upwards, illuminating the ceiling. The luminaire is equipped with a unique suspension system that facilitates the installation of the luminaire and adjustment of the suspension. All Baris 52 LED Single suspended luminaires include 1.2m long pendants with a socket in the set and are equipped with a diffuser.

APPLICATION

The luminaire is intended for indoor use. It is used as the main light source and favors office work that requires concentrated vision. The unique design, the energy-saving LED modules, and the ability to work with external lighting control systems in the DALI standard predestine the luminaire for use in modern office buildings of class A+, with a particular focus on offices, prestigious rooms, conference rooms, passageways, and wherever IP44 protection is required. Baris 52 LED Single is, as the name suggests, a single lighting element with a specific length. To create a line of length up to 6 meters without connecting the profile and up to 25 meters without connecting the lampshade, version BARIS 52 LED.

BARIS 52 LED Z 2263MM 3550LM 830 IP44 I CL. PRM

ANODA CO 32W SINGLE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|----------------------------|---|
| Index: | 468711 | Diffuser colour: | transparent |
| EAN: | 5905963468711 | Optics: | Microprism |
| Light source: | LED module | Material of the body: | aluminium |
| Rated power of the luminaire [W]: | 32 | Colour of the body: | grey |
| Luminous flux [lm]: | 3550 | Dimensions (H/W/T/S) [mm]: | 2263/69/52 |
| Supply voltage [V]: | 220 - 240 | Impact resistance: | IK06 |
| Frequency [Hz]: | 50 - 60 | Ingress protection: | IP44 |
| Luminous efficacy [lm/W]: | 112 | Mounting version: | suspended |
| Energy efficiency class: | E | Working temperature [°C]: | from -25 to +35 |
| Electrical protection class: | I | Net weight [kg]: | 2.900 |
| Colour temperature [K]: | 3000 | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Colour rendering index: | 80 | Warranty [years]: | 5 |
| SDCM: | ≤ 3 | CE certificate: | 233/2023 |
| LED lifespan L70B50 [h]: | 111500 | ENEC Certificate: | PL BBJ/006/2022/M1 |
| LED lifespan L80B20 [h]: | 70400 | PZH certificate: | B-BK-60112-0357/2023 |
| LED lifespan L90B10 [h]: | 34000 | Manual: | Download PDF |
| Diffuser material: | PC | Plik LDT: | Download |
| Diffuser type: | PRM | | |

LIGHT CURVES

