

# UV-C STERILON MAX 1500

DETAILED CARD



## TECHNICAL PARAMETERS

Nominal power [W]:	288
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	Steel
Colour of the body:	white-graphite
Ingress protection:	IP20
Dimensions (H/W/T/S) [mm]:	1895/650/650

## CHARACTERISTICS

Flow luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, mold from the surface or destroying the DNA or RNA of any exposed microorganisms. **One-pass dose from 90 J / m<sup>2</sup> to 100 J / m<sup>2</sup>. Same parameters for 800, 1200, and 1500.**

- Air-flow disinfection function
- Type of light: UV-C ultraviolet
- Steel body, powder-coated in white-graphite or black
- Light source lifespan: 9000 h
- Possibility to reset the operating time counter
- The luminaire is equipped with a LED operating time counter used for indicating the consumption of UV-C fluorescent lamps
- Very quiet operation

## APPLICATION

Luminaires are recommended for use in large service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

\* Parameters may vary (+/- 5%)

# UV-C STERILON MAX 1500

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	249969	<b>Total power consumption [W]:</b>	297
<b>Category type:</b>	bactericidal and virucidal lamps	<b>UV-C wavelength [nm]:</b>	253.70
<b>Light source:</b>	UV-C	<b>Dust filter:</b>	yes
<b>Nominal power [W]:</b>	288	<b>Flow air disinfection function:</b>	yes
<b>Supply voltage [V]:</b>	220 - 240	<b>Working time counter:</b>	yes
<b>Electrical protection class:</b>	I	<b>Air flow [m<sup>3</sup> / h]:</b>	1500
<b>Exchangeable source:</b>	yes	<b>HEPA filter holder:</b>	yes
<b>Colour of the body:</b>	white-graphite	<b>Noise intensity [dB]:</b>	37
<b>Material of the body:</b>	Steel	<b>Type of light:</b>	ultraviolet UV-C
<b>Dimensions (H/W/T/S) [mm]:</b>	1895/650/650	<b>Protection against opening:</b>	yes
<b>Cable length [m]:</b>	4	<b>Service life of the UV-C radiation source [h]:</b>	9000
<b>Ingress protection:</b>	IP20	<b>Internal element emitting UV-C radiation [W]:</b>	8x36
<b>Plug type:</b>	UNI-SCHUKO	<b>CE certificate:</b>	<a href="#">366/2023</a>
<b>Switch:</b>	yes	<b>PZH certificate:</b>	<a href="#">B-BK-60212-0535/21</a>
<b>Net weight [kg]:</b>	85	<b>Manual:</b>	<a href="#">Download PDF</a>

# UV-C STERILON MAX 1500

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
249778	HEPA filter for UV-C STERILON MAX 800/1200/1500
249785	Carbon filter for UV-STERILON MAX 800/1200/1500
249822	Pre-filter for UV-STERILON MAX 800/1200/1500
249990	Mounting bracket for UV-STERILON MAX 800/1200/1500 FILTERS

Card creation date: 03 January 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 366/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl