

# CRANE COB LED

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Nominal power [W] - range:</b>	5W COB - 1W SMD
<b>Luminous flux of the luminaire [lm] - range:</b>	620 - 120
<b>Supply voltage [V]:</b>	5
<b>Frequency [Hz]:</b>	50 - 60
<b>Luminous efficacy [lm/W]:</b>	90
<b>Energy efficiency class:</b>	G
<b>Electrical protection class:</b>	III
<b>Dimensions (H/W/T/S) [mm]:</b>	61/41.5/340

## CHARACTERISTICS

- Light source: 5W COB LED + 1W SMD LED (top)
- Luminous flux: 5W COB - 620lm, 1W SMD - 120lm
- Torchlight function
- Strong magnet in base
- Protection class: III
- Retractable rotating hook in handle
- Complete with 1.5m charging cable with C socket
- Weight: 0,30 kg
- Li-Ion 3,7V 2200mAh battery
- Lamp covered with rubber
- Charging time: 3H
- Working time: 3H (high option), 5,5H (low option)
- Indicator of battery state
- Elastic joint +/- 120°

## APPLICATION

# CRANE COB LED

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	334764	<b>Diffuser material:</b>	PC
<b>EAN:</b>	5905963334764	<b>Diffuser type:</b>	transparent
<b>Light source:</b>	5W COB LED + 1W SMD LED (upper)	<b>Colour of the body:</b>	black
<b>Nominal power [W] - range:</b>	5W COB - 1W SMD	<b>Dimensions (H/W/T/S) [mm]:</b>	61/41.5/340
<b>Luminous flux of the luminaire [lm] - range:</b>	620 - 120	<b>Ingress protection:</b>	IP44
<b>Supply voltage [V]:</b>	5	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Frequency [Hz]:</b>	50 - 60	<b>Plug type:</b>	UNI-SCHUKO
<b>Energy efficiency class:</b>	G	<b>Switch:</b>	yes
<b>Electrical protection class:</b>	III	<b>Magnet:</b>	yes
<b>Colour temperature [K]:</b>	6500	<b>Net weight [kg]:</b>	0.300
<b>Color rendering index (Ra) &gt;:</b>	80	<b>Accessories included:</b>	Complete with 1.5m charging cable with C socket
<b>Charging time [h:min]:</b>	3.00	<b>Warranty [years]:</b>	2
<b>Battery life [h:min]:</b>	3	<b>Warranty [years]:</b>	2
<b>Battery:</b>	Li-Ion 3,7V	<b>CE certificate:</b>	<a href="#">282/2023</a>
<b>Battery capacity [mAh]:</b>	2600	<b>Manual:</b>	<a href="#">Download PDF</a>

Card creation date: 16 August 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 282/2023