

FUTURE BALL 20W 230V GREY WITHOUT SOCKETS WITH ON/OFF SWITCH + MAGNET

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	20
Colour temperature [K]:	4000
Luminous flux [lm]*:	2400
Frequency [Hz]:	50 - 60
Energy efficiency class:	D
Electrical protection class:	I
Material of the body:	PP

CHARACTERISTICS

- Light source: highly efficient LED
- Power: 20W
- Total luminous flux: 2400lm
- Ingress protection class: IP 44/54
- Impact resistance class: IK10
- Even (spherical) light distribution
- Opal bowl made of PC
- Foldable hook
- Rubber cable H07RN-F 3x1,5mm (5m)
- Body: PP
- Two sockets in standard (AKKU version is equipped with one socket)
- Protective bags
- Integrated cable reel

Options:

- switch
- magnets

APPLICATION

FUTURE BALL 20W 230V GREY WITHOUT SOCKETS WITH ON/OFF SWITCH + MAGNET

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	20	Dimensions (H/W/T/S) [mm]:	244/237/236
Index:	619267	Ingress protection:	IP54
Colour temperature [K]:	4000	Impact resistance:	IK10
EAN:	5905963619267	Plug type:	UNI-SCHUCKO
Luminous flux [lm]:	2400	Working temperature [°C]:	from -20 to +35
Category type:	general construction site lighting	Wire type:	H07RN-F 3x1.5mm
Light source:	LED	Hook:	1
Supply voltage [V]:	220 - 240	Cable length [m]:	5
Frequency [Hz]:	50 - 60	Switch:	1
Luminous efficacy [lm/W]:	141	Magnet:	1
Energy efficiency class:	D	Net weight [kg]:	1.800
Electrical protection class:	I	Warranty [years]:	5
Light colour:	biały	ETIM class:	EC000346
Colour rendering index:	>80	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	266/2023
Diffuser type:	MAT	Manual:	Download PDF
Diffuser colour:	white		
Material of the body:	PP		
Colour of the body:	grey		

FUTURE BALL 20W 230V GREY WITHOUT SOCKETS WITH ON/OFF SWITCH + MAGNET

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
016707	

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 266/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl