FUTURE BALL 20W 230V GREY WITH SOCKETS DK WT. DK WITH ON/OFF + MAGNET

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	20
Colour temperature [K]:	4000
Luminous flux [lm]*:	2400
Frequency [Hz]:	50 - 60
Energy efficiency class:	D
Electrical protection class:	I
Material of the body:	PP

CHARACTERISTICS

- Light source: highly efficient LED
- Power: 20W
- Total luminous flux: 2400lm
- Ingress protection class: IP 44/54
- Impact resistance class: IK10
- Even (spherical) light distribution
- Opal bowl made of PC
- Foldable hook
- Rubber cable H07RN-F 3x1,5mm (5m)
- Body: PP
- Two sockets in standard (AKKU version is equipped with one socket)
- Protective bags
- Integrated cable reel

Options:
- switch
- magnets

APPLICATION

FUTURE BALL 20W 230V GREY WITH SOCKETS DK WT. DK WITH ON/OFF + MAGNET

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	619274
EAN:	5905963619274
Category type:	general construction site lighting
Light source:	LED
Nominal power [W]:	20
Luminous flux [lm]:	2400
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	141
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000
Light colour:	biały
Color rendering index (Ra) >:	80
Diffuser material:	PC
Diffuser type:	matt
Diffuser colour:	white
Material of the body:	PP
Colour of the body:	grey

Dimensions (H/W/T/S) [mm]:	244/237/236
Impact resistance:	IK10
Ingress protection:	IP44
Working temperature [°C]:	from -20 to +35
Plug type:	DK
Socket type:	DK
Sockets:	2
Wire type:	H07RN-F 3x1.5mm
Cable length [m]:	5
Hook:	yes
Switch:	yes
Magnet:	yes
Net weight [kg]:	1.900
Warranty [years]:	5
ETIM class:	EC000346
Warranty [years]:	5
CE certificate:	266/2023
Manual:	Download PDF

FUTURE BALL 20W 230V GREY WITH SOCKETS DK WT. DK WITH ON/OFF + MAGNET

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
016707	MAGNUM STAND - SMALL

Card creation date: 16 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 266/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl