

# FUTURE BALL 20W 230V GREY WITH SCHUCKO PLUG AND SWITCH

DETAILED CARD



## TECHNICAL PARAMETERS

|                                     |         |
|-------------------------------------|---------|
| <b>Ingress protection:</b>          | IP54    |
| <b>Impact resistance:</b>           | IK10    |
| <b>Nominal power [W]:</b>           | 20      |
| <b>Colour temperature [K]:</b>      | 4000    |
| <b>Luminous flux [lm]*:</b>         | 2400    |
| <b>Frequency [Hz]:</b>              | 50 - 60 |
| <b>Energy efficiency class:</b>     | D       |
| <b>Electrical protection class:</b> | I       |
| <b>Material of the body:</b>        | PP      |

## CHARACTERISTICS

- Light source: highly efficient LED
- Power: 20W
- Total luminous flux: 2400lm
- Ingress protection class: IP 44/54
- Impact resistance class: IK10
- Even (spherical) light distribution
- Opal bowl made of PC
- Foldable hook
- Rubber cable H07RN-F 3x1,5mm (5m)
- Body: PP
- Two sockets in standard (AKKU version is equipped with one socket)
- Protective bags
- Integrated cable reel

Options:

- switch
- magnets

## APPLICATION

# FUTURE BALL 20W 230V GREY WITH SCHUCKO PLUG AND SWITCH

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|   |                                    |                                   |                              |
|---|------------------------------------|-----------------------------------|------------------------------|
| <b>Index:</b>                           | 619212                             | <b>Colour of the body:</b>        | grey                         |
| <b>EAN:</b>                             | 5905963619212                      | <b>Dimensions (H/W/T/S) [mm]:</b> | 244/237/236                  |
| <b>Category type:</b>                   | general construction site lighting | <b>Impact resistance:</b>         | IK10                         |
| <b>Light source:</b>                    | LED                                | <b>Ingress protection:</b>        | IP54                         |
| <b>Nominal power [W]:</b>               | 20                                 | <b>Working temperature [°C]:</b>  | from -20 to +35              |
| <b>Luminous flux [lm]:</b>              | 2400                               | <b>Plug type:</b>                 | UNI-SCHUCKO                  |
| <b>Supply voltage [V]:</b>              | 220 - 240                          | <b>Socket type:</b>               | SCHUKO                       |
| <b>Frequency [Hz]:</b>                  | 50 - 60                            | <b>Sockets:</b>                   | 2                            |
| <b>Luminous efficacy [lm/W]:</b>        | 141                                | <b>Wire type:</b>                 | H07RN-F 3x1.5mm              |
| <b>Energy efficiency class:</b>         | D                                  | <b>Cable length [m]:</b>          | 5                            |
| <b>Electrical protection class:</b>     | I                                  | <b>Hook:</b>                      | yes                          |
| <b>Colour temperature [K]:</b>          | 4000                               | <b>Switch:</b>                    | yes                          |
| <b>Light colour:</b>                    | biały                              | <b>Net weight [kg]:</b>           | 1.700                        |
| <b>Color rendering index (Ra) &gt;:</b> | 80                                 | <b>Warranty [years]:</b>          | 5                            |
| <b>Diffuser material:</b>               | PC                                 | <b>ETIM class:</b>                | EC000346                     |
| <b>Diffuser type:</b>                   | matt                               | <b>Warranty [years]:</b>          | 5                            |
| <b>Diffuser colour:</b>                 | white                              | <b>CE certificate:</b>            | <a href="#">266/2023</a>     |
| <b>Material of the body:</b>            | PP                                 | <b>Manual:</b>                    | <a href="#">Download PDF</a> |

# FUTURE BALL 20W 230V GREY WITH SCHUCKO PLUG AND SWITCH

DETAILED CARD

## ACCESSORIES AVAILABLE

| index  | Name                 |
|--------|----------------------|
| 016707 | MAGNUM STAND - SMALL |

Card creation date: 16 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 266/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl