

PROFI SLIM LINE LED 24V 6X14W KIT WITH CEE PLUG

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	84
Colour temperature [K]:	4000
Luminous flux [lm]*:	10500
Supply voltage [V]:	24
Luminous efficacy [lm/W]:	125
Ingress protection:	IP65
Impact resistance:	IK10
Electrical protection class:	III
Colour rendering index:	>80
Diffuser material:	PC

CHARACTERISTICS

PROFI SLIM LINE LED is an innovative luminaire that provides a strong luminous flux, incomparably higher than in traditional fluorescent lamps. The luminaire is characterized by a compact structure (its diameter is only 20mm), thanks to which it will effectively fit into the mounting location. Luminaires are offered in selected sets with a dedicated mounting system (mounting brackets or magnets) and integrated with an easy-to-connect wiring system, connectors, and power supply. Thanks to this, you can easily create a connection configuration, and the installation of the luminaire system is intuitively simple and fast. Standardly available in sets: 2, 4, and 6 pieces.

Optional:

- color temperature: 3000K, 5700K,
- any sets.

APPLICATION

The luminaire is especially recommended for lighting car lifts, workshops, machines, and industrial surfaces.

PROFI SLIM LINE LED 24V 6X14W KIT WITH CEE PLUG

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	378942	Diffuser material:	PC
Nominal power [W]:	84	Diffuser type:	transparent
EAN:	5905963378942	Dimensions (H/W/T/S) [mm]:	ø20/1160
Luminous flux [lm]:	10500	Colour of the body:	black
Supply voltage [V]:	24	Working temperature [°C]:	from -20 to +35
Colour temperature [K]:	4000	Wire type:	H07RN-F
Version:	6x14W KIT with CEE plug	Cable length [m]:	2
Accessories included:	mounting brackets	Net weight [kg]:	3
Ingress protection:	IP65	Warranty [years]:	5
Plug type:	CEE	Additional accessories:	Uchwyty magnetyczne
Impact resistance:	IK10	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Electrical protection class:	III	CE certificate:	286/2023
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 3	Manual:	Download PDF
Beam angle [°]:	120		

PROFI SLIM LINE LED 24V 6X14W KIT WITH CEE PLUG

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
378751	PROFI SLIM LINE LED MAGNETIC HOLDER



PROFI SLIM LINE LED MAGNETIC
HOLDER (378751)

Card creation date: 14 February 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 286/2023