PROFI SLIM LINE LED 24V 6X21W KIT WITH CEE PLUG





TECHNICAL PARAMETERS

| Nominal power [W]: | 126 |
|------------------------------|-------|
| Colour temperature [K]: | 4000 |
| Luminous flux [lm]*: | 15300 |
| Supply voltage [V]: | 24 |
| Luminous efficacy [lm/W]: | 121 |
| Ingress protection: | IP65 |
| Impact resistance: | IK10 |
| Electrical protection class: | III |
| Colour rendering index: | 80 |
| Diffuser material: | PC |

CHARACTERISTICS

PROFI SLIM LINE LED is an innovative luminaire that provides a strong luminous flux, incomparably higher than in traditional fluorescent lamps. The luminaire is characterized by a compact structure (its diameter is only 20mm), thanks to which it will effectively fit into the mounting location. Luminaires are offered in selected sets with a dedicated mounting system (mounting brackets or magnets) and integrated with an easy-to-connect wiring system, connectors, and power supply. Thanks to this, you can easily create a connection configuration, and the installation of the luminaire system is intuitively simple and fast. Standardly available in sets: 2, 4, and 6 pieces.

- Optional:
- color temperature: 3000K, 5700K,
- any sets.

APPLICATION

The luminaire is especially recommended for lighting car lifts, workshops, machines, and industrial surfaces.

PROFI SLIM LINE LED 24V 6X21W KIT WITH CEE PLUG

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| Index: | 378911 | Colour of the body: | black |
|------------------------------|---------------|----------------------------|--|
| EAN: | 5905963378911 | Dimensions (H/W/T/S) [mm]: | ø20/1720 |
| Nominal power [W]: | 126 | Working temperature [°C]: | from -20 to +35 |
| Luminous flux [Im]: | 15300 | Plug type: | CEE |
| Colour temperature [K]: | 4000 | Wire type: | H07RN-F |
| Supply voltage [V]: | 24 | Cable length [m]: | 2 |
| Ingress protection: | IP65 | Accessories included: | mounting brackets |
| Impact resistance: | IK10 | Net weight [kg]: | 4.800 |
| Electrical protection class: | ш | Warranty [years]: | 5 |
| Colour rendering index: | 80 | Additional accessories: | Uchwyty magnetyczne |
| SDCM: | ≤3 | | Risk Group 1 (no photobiological hazard under normal behavioral |
| Beam angle [°]: | 120 | Photobiological safety: | limitation) |
| Diffuser material: | PC | CE certificate: | <u>286/2023</u> |
| Diffuser type: | transparent | Warranty [years]: | 5 |
| | | Manual: | Download PDF |



PROFI SLIM LINE LED 24V 6X21W KIT WITH CEE PLUG

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|-------------------------------------|
| 378751 | PROFI SLIM LINE LED MAGNETIC HOLDER |
| | |



PROFI SLIM LINE LED MAGNETIC HOLDER (378751)

Card creation date: 14 February 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

Certificate CE - Nr: 286/2023

This product is a subject to electric and electronic waste equipment regulations (WEEE).



A