DETAILED CARD





TECHNICAL PARAMETERS

Light source: LED

Luminous flux [lm]*: 300

Supply voltage [V]: 3.7

Electrical protection class:

Light colour: biały

Colour rendering index: >80

Diffuser type: transparent

Dimensions (H/W/T/S) [mm]: 78/475/42

Impact resistance: IK07

Working temperature [°C]: from -20 to +35

CHARACTERISTICS

- Light source: COB LED

- ACCU mode working types:

• 300lm - 2,5h working time

• 100lm - 4h working time

- Elastic top joint 60°

- Protection class: III

- The set includes USB-C cable

- Dimensions: 260x75x75mm

- Weight: 110 g

- Li-lon 3,7V 1500mAh battery

- Charging time: 3H

- Indicator of battery state

- Turning on the lamp by hand movement thanks to included sensor

- Non-skid belt

- Modern design and top quality

APPLICATION



DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	334689
EAN:	5905963334689
Light source:	LED
Luminous flux [lm]:	300
Supply voltage [V]:	3.7
Electrical protection class:	III
Light colour:	biały
Colour rendering index:	>80
Diffuser type:	transparent
Dimensions (H/W/T/S) [mm]:	78/475/42

Impact resistance:	IK07
Working temperature [°C]:	from -20 to +35
Switch:	yes
Net weight [kg]:	0.110
Warranty [years]:	2
Accessories included:	USB-C cable
Warranty [years]:	2
CE certificate:	287/2023
Manual:	Download PDF

Card creation date: 25 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

