CYCLOP LED

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED
Luminous flux [lm]*:	300
Supply voltage [V]:	3.7
Electrical protection class:	III
Light colour:	biały
Color rendering index (Ra) >:	80
Diffuser type:	transparent
Dimensions (H/W/T/S) [mm]:	78/475/42
Impact resistance:	IK07
Working temperature [°C]:	from -20 to +35

CHARACTERISTICS

- Light source: COB LED
- ACCU mode working types:
    - 300lm - 2,5h working time
    - 100lm - 4h working time
- Elastic top joint 60°
- Protection class: III
- The set includes USB-C cable
- Dimensions: 260x75x75mm
- Weight: 110 g
- Li-Ion 3,7V 1500mAh battery
- Charging time: 3H
- Indicator of battery state
- Turning on the lamp by hand movement thanks to included sensor
- Non-skid belt
- Modern design and top quality

APPLICATION

CYCLOP LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	334689	**Impact resistance:**	IK07
EAN:	5905963334689	**Working temperature [°C]:**	from -20 to +35
Light source:	LED	**Switch:**	yes
Luminous flux [lm]:	300	**Net weight [kg]:**	0.110
Supply voltage [V]:	3.7	**Warranty [years]:**	2
Electrical protection class:	III	**Accessories included:**	USB-C cable
Light colour:	biały	**Warranty [years]:**	2
Color rendering index (Ra) >:	80	**CE certificate:**	287/2023
Diffuser type:	transparent	**Manual:**	Download PDF
Dimensions (H/W/T/S) [mm]:	78/475/42		

Card creation date: 11 August 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 287/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl