

PROFI SLIM LED 12W 230V 4000K

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	12
Colour temperature [K]:	4000
Ingress protection:	IP44
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	II
Color rendering index (Ra) >:	80

CHARACTERISTICS

- Power: 12W
- Light source: SMD LED
- High ingress protection class IP44
- Polycarbonate diffuser
- Handle and cap made of ABS
- Weight: 0,6kg
- Rubber cable: H05RR-F 2x0,1mm² (5m)
- Spare parts available

APPLICATION

PROFI SLIM LED 12W 230V 4000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	378157	Dimensions (H/W/T/S) [mm]:	35/850
EAN:	5905963378157	Impact resistance:	IK09
Light source:	LED	Ingress protection:	IP44
Nominal power [W]:	12	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220 - 240	Plug type:	UNI-SCHUKO
Frequency [Hz]:	50 - 60	Wire type:	H05RR-F
Electrical protection class:	II	Cable length [m]:	5
Colour temperature [K]:	4000	Hook:	yes
Color rendering index (Ra) >:	80	Net weight [kg]:	0.600
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	matt	Warranty [years]:	5
Material of the body:	ABS	CE certificate:	290/2023
Colour of the body:	black	Manual:	Download PDF

Card creation date: 19 November 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 290/2023