

PROFI SLIM LED 24W 230V 4000K

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	24
Colour temperature [K]:	4000
Ingress protection:	IP44
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	II
Color rendering index (Ra) >:	80
Material of the body:	ABS
Dimensions (H/W/T/S) [mm]:	35/850
Warranty [years]:	5

CHARACTERISTICS

- Power: 24W
- Light source: SMD LED
- High ingress protection class IP44
- Polycarbonate diffuser
- Handle and cap made of ABS
- Weight: 0,7kg
- Rubber cable: H05RR-F 2x0,1mm2 (5m)
- Spare parts available

APPLICATION

PROFI SLIM LED 24W 230V 4000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	378164	Dimensions (H/W/T/S) [mm]:	35/850
EAN:	5905963378164	Impact resistance:	IK09
Light source:	LED	Ingress protection:	IP44
Nominal power [W]:	24	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220 - 240	Plug type:	UNI-SCHUKO
Frequency [Hz]:	50 - 60	Wire type:	H05RR-F
Electrical protection class:	II	Cable length [m]:	5
Colour temperature [K]:	4000	Hook:	yes
Color rendering index (Ra) >:	80	Net weight [kg]:	0.700
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	matt	Warranty [years]:	5
Material of the body:	ABS	CE certificate:	290/2023
Colour of the body:	black	Manual:	Download PDF

Card creation date:19 November 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 290/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl