

# OCULUS LED MINI UGR 11300LM 840 IP66 I CL. SP10KV 74W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK08
<b>Rated power of the luminaire [W]*:</b>	74
<b>Luminous flux [lm]*:</b>	11300
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Electrical protection class:</b>	I
<b>Material of the body:</b>	powder coated aluminium
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

A HIGH-BAY luminaire from the NEXT GEN product line, constituting a new generation of luminaires dedicated to LED technology. The designed-from-scratch body – made of die-cast aluminium and powder-coated – uses natural conduction and convection processes, which have a positive effect on the luminaire's heat management. The shape of the body with an integrated, effective heat sink and high-quality materials ensure maximum heat dissipation from the LED module. The driver's external compartment, separated from the body, guarantees optimal thermal working conditions for the power supply system. This enables the luminaire to work at an ambient temperature of max 55°C. LEDs from a reputable manufacturer and new LED modules enable very high luminous efficiency. This guarantees that the required lighting level and significant energy savings are achieved. The diffuser and optical system are composed of precise lenses made of polycarbonate (PC). Standard equipped with a 0.3 m long H07RN-F cable terminated with an additional male and female connector, which makes the assembly easier and more convenient. Its design is adapted for suspended mounting and surface mounting (ceiling and wall) requiring the use of additional accessories.

A UGR (Unified Glare Rating) of less than 19 minimizes the effect of glare affecting well-being, reducing fatigue and fewer mistakes.

## APPLICATION

The luminaire is designed for suspended mounting using chains, ropes, etc. and with the use of additional accessories also surface-mounted (ceiling and wall) indoors. It works perfectly in factories and production halls as well as large-scale warehouses and logistics centers.

# OCULUS LED MINI UGR 11300LM 840 IP66 I CL. SP10KV 74W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	74	Optics material:	PC
Index:	561306	Optics:	lens
Colour temperature [K]:	4000	Material of the body:	powder coated aluminium
Luminous flux [lm]:	11300	Colour of the body:	grey
Supply voltage [V]:	220 - 240	Dimensions (H/W/T/S) [mm]:	107/320
Frequency [Hz]:	50 - 60	Impact resistance:	IK08
Luminous efficacy [lm/W]:	152	Ingress protection:	IP66
Energy efficiency class:	C	Working temperature [°C]:	55
Electrical protection class:	I	Mounting version:	surface, suspended
Colour rendering index:	>80	Cable length [m]:	0.30
SDCM:	≤ 3	Net weight [kg]:	2.330
Power factor:	0.98	Warranty [years]:	5
LED lifespan L70B50 [h]:	196000	Warranty [years]:	5
LED lifespan L80B20 [h]:	123000	CE certificate:	<a href="#">157/2023</a>
LED lifespan L90B10 [h]:	60000	PZH certificate:	<a href="#">B-BK-60212-0481/21</a>
Beam angle [°]:	55	Manual:	<a href="#">Download PDF</a>
Surge protection [kV]:	4	Additional accessories:	OCULUS LED MINI- RCR sensor - complete (967054)
Diffuser material:	PC	Plik LDT:	
Diffuser type:	transparent		
Diffuser colour:	transparent		

# OCULUS LED MINI UGR 11300LM 840 IP66 I CL. SP10KV 74W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
964886	OCULUS LED - universal handle-lack of compatibility with Dali version 294W
964893	OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W
WSEL438	Remote control for motion sensor HD01R
WSEL415	WSEL415 Remote control for - PIR sensor
967054	OCULUS LED MINI- RCR sensor -complete
967047	OCULUS LED MINI- PIR / RCR DALI sensor complete
561399	OCULUS LED MINI- safety net kit
561382	OCULUS LED- safety net kit




OCULUS LED - universal handle-lack of compatibility with Dali version 294W (964886)



OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W (964893)



Remote control for motion sensor HD01R (WSEL438)




WSEL415 Remote control for - PIR sensor (WSEL415)



OCULUS LED MINI- RCR sensor - complete (967054)



OCULUS LED MINI- PIR / RCR DALI sensor complete (967047)



OCULUS LED MINI- safety net kit (561399)



OCULUS LED- safety net kit (561382)

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 157/2023