

IQ SUN MED PRO WHITE MAT

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|-------------|
| Rated power of the luminaire [W]*: | 44 |
| Luminous flux [lm]*: | 4950 |
| Colour temperature [K]: | 5600 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Diffuser material: | PC |
| Diffuser type: | MAT |
| Diffuser colour: | white |
| Colour of the body: | white |
| Dimensions (H/W/T/S) [mm]: | 375/320/165 |

CHARACTERISTICS

Luminaires that improve mood, balance and body performance. Therapeutic mode - 30 minutes of lighting with the intensity of 5000 lux at a distance of 50 cm. Make multiple such sessions as needed. IQ Sun Med Pro Features:- therapeutic function: 5000 lux at a distance of 50 cm;- LCD display;- smooth light regulation;- 10 power levels, which allows you to adjust to your body and your needs;- the ability to set the working time;- has a light wake-up function;- has the function of falling asleep with the light;- intuitive menu;- watch;- therapy time display/counter;- LED technology;- energy-saving

APPLICATION

It will work:

- for people suffering from fall/winter depression, malaise
- sleep disturbances
- disturbance in concentration
- for women who have had a baby (Baby Blues)
- for people who want to improve their body performance
- for people doing intellectual work - can be used in the workplace
- ideal solution for people studying, for example for exams
- For people who frequently change time zones to reduce discomfort

IQ SUN MED PRO WHITE MAT

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|------------------------------|---|
| Index: | 660917 | Material of the body: | ABS |
| Nominal power [W]: | 42 | Colour of the body: | white |
| Rated power of the luminaire [W]: | 44 | Dimensions (H/W/T/S) [mm]: | 375/320/165 |
| Colour temperature [K]: | 5600 | Impact resistance: | IK07 |
| Luminous flux [lm]: | 4950 | Ingress protection: | IP20 |
| Supply voltage [V]: | 220 - 240 | Working temperature [°C]: | from -20 to +35 |
| Frequency [Hz]: | 50 - 60 | Plug type: | UNI-SCHUKO |
| Luminous efficacy [lm/W]: | 112 | Control: | Yes - buttons |
| Electrical protection class: | I | Wire type: | H05VV-F |
| Colour rendering index: | >80 | Cable length [m]: | 2 |
| SDCM: | ≤ 3 | Number on the palette [pcs]: | 30 |
| LED lifespan L70B50 [h]: | 132000 | Net weight [kg]: | 2.800 |
| LED lifespan L80B20 [h]: | 84000 | Warranty [years]: | 5 |
| LED lifespan L90B10 [h]: | 42000 | Warranty [years]: | 5 |
| Beam angle [°]: | 115 | CE certificate: | 89/2023 |
| Light distribution type: | lambertian | Manual: | Download PDF |
| Diffuser material: | PC | Category type: | Lamps with a positive effect on the mood |
| Diffuser type: | MAT | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Diffuser colour: | white | | |

Card creation date: 27 May 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 89/2023