

TAURUS SMD LED 40W 24V WITH CEE SOCKETS

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	40
Colour temperature [K]:	4000
Supply voltage [V]:	24
Electrical protection class:	III
Material of the body:	PP
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	MAT

CHARACTERISTICS

- Light source: highly efficient SMD LED
- Power: 40W
- Ingress protection class: IP54, IP44
- Impact-resistant casing and multi-positional arm
- Anti-glare diffuser made of frozen polycarbonate
- Wide lighting angle (120°)
- Rubber cable H07RN-F 2x1,0mm² (5m)
- Weight: 3,2kg - 3,4kg

Optionally available:

- Two sockets at the backside of the fitting
- Rubber cable H07RN-F 3x1,5mm² (5m)

APPLICATION

TAURUS SMD LED 40W 24V WITH CEE SOCKETS

DETAILED CARD


TECHNICAL PARAMETERS TABLE

Index:	291944	Ingress protection:	IP44
EAN:	5905963291944	Working temperature [°C]:	from -20 to +35
Light source:	LED	Plug type:	CEE
Nominal power [W]:	40	Socket type:	CEE (2-PIN)
Colour temperature [K]:	4000	Sockets:	2
Supply voltage [V]:	24	Wire type:	H07RN-F
Electrical protection class:	III	Cable length [m]:	5
Colour rendering index:	>80	Net weight [kg]:	3.400
Light colour:	biały	Warranty [years]:	2
Diffuser material:	PC	Category type:	workplace floodlights
Diffuser type:	MAT	ETIM class:	EC000347
Diffuser colour:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	PP	CE certificate:	142/2023
Colour of the body:	grey	Warranty [years]:	2
Dimensions (H/W/T/S) [mm]:	373/312/125	Manual:	Download PDF
Impact resistance:	IK10		

Card creation date: 17 December 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 142/2023