TAURUS SMD LED 40W 24V WITH CEE SOCKETS

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	40
Colour temperature [K]:	4000
Supply voltage [V]:	24
Electrical protection class:	III
Material of the body:	PP
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	matt

CHARACTERISTICS

- Light source: highly efficient SMD LED
- Power: 40W
- Ingress protection class: IP54, IP44
- Impact-resistant casing and multi-positional arm
- Anti-glare diffuser made of frozen polycarbonate
- Wide lighting angle (120°)
- Rubber cable H07RN-F 2x1,0mm2 (5m)
- Weight: 3,2kg - 3,4kg

Optionally available:

- Two sockets at the backside of the fitting
- Rubber cable H07RN-F 3x1,5mm2 (5m)

APPLICATION

TAURUS SMD LED 40W 24V WITH CEE SOCKETS

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	291944	**Ingress protection:**	IP44
EAN:	5905963291944	**Working temperature [°C]:**	from -20 to +35
Light source:	LED	**Plug type:**	CEE
Nominal power [W]:	40	**Socket type:**	CEE (2-PIN)
Colour temperature [K]:	4000	**Sockets:**	2
Supply voltage [V]:	24	**Wire type:**	H07RN-F
Electrical protection class:	III	**Cable length [m]:**	5
Color rendering index (Ra) >:	80	**Net weight [kg]:**	3.400
Light colour:	biały	**Warranty [years]:**	2
Diffuser material:	PC	**Category type:**	workplace floodlights
Diffuser type:	matt	**ETIM class:**	EC000347
Diffuser colour:	white	**Photobiological safety:**	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	PP		
Colour of the body:	grey	**CE certificate:**	142/2023
Dimensions (H/W/T/S) [mm]:	373/312/125	**Warranty [years]:**	2
Impact resistance:	IK10	**Manual:**	Download PDF

Card creation date: 17 December 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 142/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl