TAURUS SMD LED 40W 42V CEE

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	40
Colour temperature [K]:	4000
Supply voltage [V]:	42
Electrical protection class:	III
Material of the body:	PP
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	matt

CHARACTERISTICS

- Light source: highly efficient SMD LED
- Power: 40W
- Ingress protection class: IP54, IP44
- Impact-resistant casing and multi-positional arm
- Anti-glare diffuser made of frozen polycarbonate
- Wide lighting angle (120°)
- Rubber cable H07RN-F 2x1,0mm2 (5m)
- Weight: 3,2kg - 3,4kg

Optionally available:

- Two sockets at the backside of the fitting
- Rubber cable H07RN-F 3x1,5mm2 (5m)

APPLICATION

TAURUS SMD LED 40W 42V CEE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	291890
EAN:	5905963291890
Light source:	LED
Nominal power [W]:	40
Colour temperature [K]:	4000
Supply voltage [V]:	42
Electrical protection class:	III
Color rendering index (Ra) >:	80
Light colour:	biały
Diffuser material:	PC
Diffuser type:	matt
Diffuser colour:	white
Material of the body:	PP
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	373/312/125

Impact resistance:	IK10
Ingress protection:	IP44
Working temperature [°C]:	from -20 to +35
Plug type:	CEE
Wire type:	H07RN-F
Cable length [m]:	5
Net weight [kg]:	3.200
Warranty [years]:	2
Category type:	workplace floodlights
ETIM class:	EC000347
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
CE certificate:	142/2023
Warranty [years]:	2
Manual:	Download PDF

Card creation date: 26 November 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 142/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl