

# TAURUS SMD LED 40W DK SWITCH

DETAILED CARD



## TECHNICAL PARAMETERS

|                                     |           |
|-------------------------------------|-----------|
| <b>Ingress protection:</b>          | IP44      |
| <b>Impact resistance:</b>           | IK10      |
| <b>Nominal power [W]:</b>           | 40        |
| <b>Colour temperature [K]:</b>      | 4000      |
| <b>Supply voltage [V]:</b>          | 220 - 240 |
| <b>Electrical protection class:</b> | II        |
| <b>Material of the body:</b>        | PP        |
| <b>Colour of the body:</b>          | grey      |
| <b>Diffuser material:</b>           | PC        |
| <b>Diffuser type:</b>               | MAT       |

## CHARACTERISTICS

- Light source: highly efficient SMD LED
- Power: 40W
- Ingress protection class: IP54, IP44
- Impact-resistant casing and multi-positional arm
- Anti-glare diffuser made of frozen polycarbonate
- Wide lighting angle (120°)
- Rubber cable H07RN-F 2x1,0mm<sup>2</sup> (5m)
- Weight: 3,2kg - 3,4kg

Optionally available:

- Two sockets at the backside of the fitting
- Rubber cable H07RN-F 3x1,5mm<sup>2</sup> (5m)

## APPLICATION

# TAURUS SMD LED 40W DK SWITCH

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                              |               |                            |   |
|------------------------------|---------------|----------------------------|---|
| Nominal power [W]:           | 40            | Dimensions (H/W/T/S) [mm]: | 373/312/125   |
| Index:                       | 291975        | Diffuser colour:           | white   |
| Colour temperature [K]:      | 4000          | Material of the body:      | PP  |
| EAN:                         | 5905963291975 | Colour of the body:        | grey  |
| Ingress protection:          | IP44          | Impact resistance:         | IK10  |
| Light source:                | LED           | Working temperature [°C]:  | from -20 to +35   |
| Plug type:                   | DK            | Wire type:                 | H07RN-F   |
| Supply voltage [V]:          | 220 - 240     | Cable length [m]:          | 5   |
| Frequency [Hz]:              | 50 - 60       | Net weight [kg]:           | 3.200   |
| Electrical protection class: | II            | Warranty [years]:          | 2   |
| Colour rendering index:      | >80           | Category type:             | workplace floodlights   |
| Switch:                      | yes           | ETIM class:                | EC000347  |
| Light colour:                | biały         | Photobiological safety:    | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Diffuser material:           | PC            | CE certificate:            | <a href="#">143/2023</a>  |
| Diffuser type:               | MAT           | Warranty [years]:          | 2   |
|                              |               | Manual:                    | <a href="#">Download PDF</a>  |

Card creation date: 17 December 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 143/2023