

TAURUS SMD LED 40W WITH DK SOCKETS

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|-------------------------------------|-----------|
| Ingress protection: | IP44 |
| Impact resistance: | IK10 |
| Nominal power [W]: | 40 |
| Colour temperature [K]: | 4000 |
| Supply voltage [V]: | 220 - 240 |
| Electrical protection class: | I |
| Material of the body: | PP |
| Colour of the body: | grey |
| Diffuser material: | PC |
| Diffuser type: | MAT |

CHARACTERISTICS

- Light source: highly efficient SMD LED
- Power: 40W
- Ingress protection class: IP54, IP44
- Impact-resistant casing and multi-positional arm
- Anti-glare diffuser made of frozen polycarbonate
- Wide lighting angle (120°)
- Rubber cable H07RN-F 2x1,0mm² (5m)
- Weight: 3,2kg - 3,4kg

Optionally available:

- Two sockets at the backside of the fitting
- Rubber cable H07RN-F 3x1,5mm² (5m)

APPLICATION

TAURUS SMD LED 40W WITH DK SOCKETS

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|------------------------------|---------------|----------------------------|---|
| Nominal power [W]: | 40 | Dimensions (H/W/T/S) [mm]: | 373/312/125 |
| Index: | 291821 | Diffuser colour: | white |
| Colour temperature [K]: | 4000 | Material of the body: | PP |
| EAN: | 5905963291821 | Colour of the body: | grey |
| Ingress protection: | IP44 | Impact resistance: | IK10 |
| Light source: | LED | Working temperature [°C]: | from -20 to +35 |
| Plug type: | DK | Wire type: | H07RN-F |
| Socket type: | DK | Cable length [m]: | 5 |
| Supply voltage [V]: | 220 - 240 | Net weight [kg]: | 3.400 |
| Sockets: | 2 | Warranty [years]: | 2 |
| Frequency [Hz]: | 50 - 60 | Category type: | workplace floodlights |
| Electrical protection class: | I | ETIM class: | EC000347 |
| Colour rendering index: | >80 | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Light colour: | biały | CE certificate: | 143/2023 |
| Diffuser material: | PC | Warranty [years]: | 2 |
| Diffuser type: | MAT | Manual: | Download PDF |

Card creation date: 17 December 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 143/2023