

# TAURUS SMD LED 40W WITH SCHUKO SOCKETS SWITCH

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP54
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	40
<b>Colour temperature [K]:</b>	4000
<b>Supply voltage [V]:</b>	220 - 240
<b>Electrical protection class:</b>	I
<b>Material of the body:</b>	PP
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	MAT

## CHARACTERISTICS

- Light source: highly efficient SMD LED
- Power: 40W
- Ingress protection class: IP54, IP44
- Impact-resistant casing and multi-positional arm
- Anti-glare diffuser made of frozen polycarbonate
- Wide lighting angle (120°)
- Rubber cable H07RN-F 2x1,0mm<sup>2</sup> (5m)
- Weight: 3,2kg - 3,4kg

Optionally available:

- Two sockets at the backside of the fitting
- Rubber cable H07RN-F 3x1,5mm<sup>2</sup> (5m)

## APPLICATION

# TAURUS SMD LED 40W WITH SCHUKO SOCKETS SWITCH

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	291883	<b>Ingress protection:</b>	IP54
<b>EAN:</b>	5905963291883	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Light source:</b>	LED	<b>Plug type:</b>	UNI-SCHUKO
<b>Nominal power [W]:</b>	40	<b>Socket type:</b>	UNI-SCHUKO
<b>Colour temperature [K]:</b>	4000	<b>Sockets:</b>	2
<b>Supply voltage [V]:</b>	220 - 240	<b>Wire type:</b>	H07RN-F
<b>Frequency [Hz]:</b>	50 - 60	<b>Cable length [m]:</b>	5
<b>Electrical protection class:</b>	I	<b>Switch:</b>	yes
<b>Colour rendering index:</b>	>80	<b>Net weight [kg]:</b>	3.400
<b>Light colour:</b>	biały	<b>Warranty [years]:</b>	2
<b>Diffuser material:</b>	PC	<b>Category type:</b>	workplace floodlights
<b>Diffuser type:</b>	MAT	<b>ETIM class:</b>	EC000347
<b>Diffuser colour:</b>	white	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Material of the body:</b>	PP	<b>CE certificate:</b>	<a href="#">143/2023</a>
<b>Colour of the body:</b>	grey	<b>Warranty [years]:</b>	2
<b>Dimensions (H/W/T/S) [mm]:</b>	373/312/125	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Impact resistance:</b>	IK10		

Card creation date: 17 December 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 143/2023