



TECHNICAL PARAMETERS

Index:	514890
Ingress protection:	IP20
Nominal power [W]:	35
Luminous flux [lm]*:	4650
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	D
Optics:	lens
Mounting version:	recessed

CHARACTERISTICS

The surface, recessed or suspended (suspension system as a accessories) mounted fixture equipped with energy saving LED GO panels and a lens generating asymmetric light distribution. It was made of powder coated white RAL 9003 steel sheet. Shade – a PMMA iridescent lens of 85% light transmission assures high efficiency of the fixture. Available in two power options: 35W with a single LED GO! Panel and 70W with a double LED GO! panel. Colour temperature: 3000K or 4000K. Fixture's colour rendering index is: CRI>80 and standard deviation colour matching (SDCM): ≤ 3, assuring homogeneity and uniformity of light. Suspension of the luminaire is possible, thanks to special suspension system (accessories).


APPLICATION

The fixture is equipped with linear lenses assuring asymmetric distribution with a beam angle of 20° that is perfect for illumination of boards, paintings and display cases. An iridescent lampshade disperses light assuring that objects are uniformly illuminated with no light reflex. The fixture is applied mostly in schools, universities, museums and art galleries.

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Material of the body:	steel
Nominal power [W]:	35	Colour of the body:	white
Rated power of the luminaire [W]:	38.40	Dimensions (H/W/T/S) [mm]:	85/1435/60
Supply voltage [V]:	220-240	Mounting dimensions [mm]:	1410/65
Frequency [Hz]:	50 - 60	Ingress protection:	IP20
Luminous flux [lm]:	4650	Mounting version:	recessed
Luminous efficacy [lm/W]:	121	Working temperature [°C]:	from 0 to +35
Energy efficiency class:	D	Net weight [kg]:	2.550
Electrical protection class:	I	CE certificate:	308/2023
Colour temperature [K]:	4000	Index:	514890
Colour rendering index:	>80	Category type:	battens
SDCM:	≤ 3	LED lifespan L70B50 [h]:	50000
Power factor:	0.98	Warranty [years]:	5
Exchangeable source:	yes	ETIM class:	EC000109
Optics material:	PMMA	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics:	lens	Manual:	Download PDF

LIGHT CURVES



ACCESSORIES AVAILABLE

index	Name
171512	SINGLE SUSPENDE CORD
171635	SINGLE SUSPENDE CORD (ROUND BOX)
171642	SINGLE SUSPENDE CORD (SQUARE BOX)
171703	SINGLE ELECTRICAL SUSPENDE CORD (ROUND BOX) TABLO NT
171710	SINGLE ELECTRICAL SUSPENDE CORD (SQUARE BOX) TABLO NT



SINGLE SUSPENDE CORD (171512)



SINGLE SUSPENDE CORD (ROUND BOX) (171635)



SINGLE SUSPENDE CORD (SQUARE BOX) (171642)



SINGLE ELECTRICAL SUSPENDE CORD (ROUND BOX) TABLO NT (171703)



SINGLE ELECTRICAL SUSPENDE CORD (SQUARE BOX) TABLO NT (171710)

Card creation date: 21 March 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 308/2023