

PROFI LED 5W

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	5
Luminous flux [lm]*:	700
Ingress protection:	IP54
Supply voltage [V]:	24
Electrical protection class:	III
Colour rendering index:	>80
Material of the body:	gum
Dimensions (H/W/T/S) [mm]:	60/415

CHARACTERISTICS

- Power: 4W, 5W
- Luminous flux: 450lm, 700lm
- 65% less power consumption (compared to Profi 11W)
- Light source: SMD LED
- Polycarbonate impact-resistant prismatic diffuser
- Handle and cap made of rubber
- High ingress protection class IP54
- Rotating hook
- Weight: 0,7 kg
- Rubber cable H05RN-F 2x1 mm2 (5m)
- Spare parts available

APPLICATION

PROFI LED 5W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	380990	Colour of the body:	black
EAN:	5905963380990	Dimensions (H/W/T/S) [mm]:	60/415
Light source:	LED	Ingress protection:	IP54
Nominal power [W]:	5	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	700	Plug type:	TRAFO
Supply voltage [V]:	24	Hook:	yes
Electrical protection class:	III	Net weight [kg]:	0.700
Colour rendering index:	>80	Warranty [years]:	2
Diffuser material:	PC	Warranty [years]:	2
Diffuser type:	transparent	CE certificate:	259/2023
Material of the body:	gum	Manual:	Download PDF

PROFI LED 5W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
111631	
886584	Magnetic rubber mount



Magnetic rubber mount (886584)

Card creation date: 01 December 2021
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 259/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl