

# TYTAN 2 LED BASIC 1450MM 10600LM 840 IP66 AW3H 74W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	912535
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK09
<b>Rated power of the luminaire [W]*:</b>	74
<b>Luminous flux [lm]*:</b>	10600
<b>Colour temperature [K]:</b>	4000
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	PC
<b>Colour of the body:</b>	RAL7035
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

TYTAN 2 LED BASIC is a basic line of lighting fixtures which provides an excellent alternative to traditional fluorescent lamps. The lighting fixture has been designed from scratch. TYTAN 2 LED BASIC includes new solutions which improve the light distribution and the temperature balance. The new LED panels ensure high luminous efficacy of <math><150\text{lm/W}</math>. This provides the required level of lighting along with significant energy savings. The lighting fixture includes many improvements which facilitate and speed up the installation process: a solution involving the integration of the diffuser with the LED panel, a diffuser suspension system, and adjustable mounting brackets with an installation tolerance of  $\pm 50$  mm. As a standard, the fixture is equipped with robust clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation.

## APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.


# TYTAN 2 LED BASIC 1450MM 10600LM 840 IP66 AW3H 74W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	74	Colour of the body:	RAL7035
Index:	912535	Mounting dimensions [mm]:	970
EAN:	5905963912535	Impact resistance:	IK09
Colour temperature [K]:	4000	Ingress protection:	IP66
Light source:	LED module	Mounting version:	surface, suspended
Luminous flux [lm]:	10600	Working temperature [°C]:	from 0 to +35
Rated power of the luminaire [W]:	74	Net weight [kg]:	1.200
Emergency lighting [h]:	3	Category type:	battens
Supply voltage [V]:	220 - 240	Autotest:	yes
Frequency [Hz]:	50 - 60	AC voltage range [V]:	198 - 264
Dimensions (H/W/T/S) [mm]:	1432/85/80	LED lifespan L70B50 [h]:	90000
Luminous efficacy [lm/W]:	143	LED lifespan L80B20 [h]:	57000
Energy efficiency class:	C	LED lifespan L90B10 [h]:	27000
Electrical protection class:	I	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Colour rendering index:	>80	Category of application:	commercial facilities, industrial
SDCM:	≤ 3	Mark D:	yes
Power factor:	0.98	Warranty [years]:	2 / 0.5 (battery)
Battery life [h:min]:	3	CE certificate:	<a href="#">274/2023</a>
Surge protection [kV]:	1	ENEC Certificate:	<a href="#">0310/ENEC/23</a>
Diffuser material:	PC	PZH certificate:	<a href="#">B-BK-60212-0152/20</a>
Diffuser type:	MAT	HACCP:	<a href="#">852/2004</a>
Material of the body:	PC	Manual:	<a href="#">Download PDF</a>
		Optics material:	PC
		Additional accessories:	protective grid, adjustable handle
		Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES



# TYTAN 2 LED BASIC 1450MM 10600LM 840 IP66 AW3H 74W

DETAILED CARD

## TECHNICAL DETAILS



regulowane uchwyty / adjustable handles / einstellbare Halterungen



system zwieszania klosza / suspension system of the diffuser / hängende Diffusor




wybór miejsca zasilania / choosing a place of power supply / Stromversorgungsanschluss von mehreren Seite möglich

# TYTAN 2 LED BASIC 1450MM 10600LM 840 IP66 AW3H 74W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
907913	TYTAN LED. ATLAS LED - protective grid 1152mm
907920	TYTAN LED. ATLAS LED - protective grid 1432mm
16000507	Breathable gland gray M20*1.5 IP68
60000006	M16 stuffing box plug various PA black M-16 - BPM-21



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



TYTAN LED. ATLAS LED - protective grid 1152mm (907913)



TYTAN LED. ATLAS LED - protective grid 1432mm (907920)



Breathable gland gray M20\*1.5 IP68 (16000507)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 274/2023