

TYTAN 2 LED BASIC 1450MM 10600LM 840 IP66 LS2 (2.5) 74W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	912559
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	74
Luminous flux [lm]*:	10600
Colour temperature [K]:	4000
Energy efficiency class:	C
Material of the body:	PC
Colour of the body:	RAL7035
Diffuser material:	PC

CHARACTERISTICS

TYTAN 2 LED BASIC is a basic line of lighting fixtures which provides an excellent alternative to traditional fluorescent lamps. The lighting fixture has been designed from scratch. TYTAN 2 LED BASIC includes new solutions which improve the light distribution and the temperature balance. The new LED panels ensure high luminous efficacy of <math><150\text{lm/W}</math>. This provides the required level of lighting along with significant energy savings. The lighting fixture includes many improvements which facilitate and speed up the installation process: a solution involving the integration of the diffuser with the LED panel, a diffuser suspension system, and adjustable mounting brackets with an installation tolerance of ± 50 mm. As a standard, the fixture is equipped with robust clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation.

APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.

TYTAN 2 LED BASIC 1450MM 10600LM 840 IP66 LS2 (2.5) 74W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	912559	Working temperature [°C]:	from -20 to +35
EAN:	5905963912559	Through wiring:	LS2
Light source:	LED module	Net weight [kg]:	1.200
Rated power of the luminaire [W]:	74	Category type:	battens
Supply voltage [V]:	220 - 240	AC voltage range [V]:	198 - 264
Frequency [Hz]:	50 - 60	LED lifespan L70B50 [h]:	90000
Luminous flux [lm]:	10600	LED lifespan L80B10 [h]:	57000
Luminous efficacy [lm/W]:	143	LED lifespan L90B10 [h]:	27000
Energy efficiency class:	C	Category of application:	industrial, commercial facilities
Electrical protection class:	I	Mark D:	yes
Colour temperature [K]:	4000	Wire type:	5x2,5
Color rendering index (Ra) >:	80	Optics material:	PC
SDCM:	3	Additional accessories:	protective grid, adjustable handle
Power factor:	0.98	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Surge protection [kV]:	1	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	274/2023
Diffuser type:	matt	ENEC Certificate:	0310/ENEC/23
Material of the body:	PC	HACCP:	852/2004
Colour of the body:	RAL7035	PZH certificate:	B-BK-60112-0280/2025
Dimensions (H/W/T/S) [mm]:	1432/85/80	Environmental Product Declaration (EPD):	944/2026
Mounting dimensions [mm]:	970	Manual:	Download PDF
Impact resistance:	IK09	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Ingress protection:	IP66	Plik LDT:	Download
Mounting version:	surface, suspended		

TECHNICAL DETAILS



regulowane uchwyty / adjustable handles / einstellbare Halterungen



system zwieszania klosza / suspension system of the diffuser / hängende Diffusor



wybór miejsca zasilania / choosing a place of power supply / Stromversorgungsanschluss von mehreren Seite möglich

TYTAN 2 LED BASIC 1450MM 10600LM 840 IP66 LS2 (2.5) 74W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
907913	TYTAN LED. ATLAS LED - protective grid 1152mm
907920	TYTAN LED. ATLAS LED - protective grid 1432mm
16000507	Breathable gland gray M20*1.5 IP68
60000006	M16 stuffing box plug various PA black M-16 - BPM-21



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



TYTAN LED. ATLAS LED - protective grid 1152mm (907913)



TYTAN LED. ATLAS LED - protective grid 1432mm (907920)



Breathable gland gray M20*1.5 IP68 (16000507)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 04 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 274/2023