

QUEST 2 LED M 21000LM I CL. IP66 730 SP10KV (184W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	696008
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	184
Luminous flux [lm]*:	21000
Colour temperature [K]:	3000
Colour rendering index:	70
SDCM:	≤ 5
Electrical protection class:	I
Energy efficiency class:	E

CHARACTERISTICS

High-quality floodlight with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass. It is equipped with directional lens matrices with 3 different light distributions: symmetrical (120°), asymmetric narrow ASN and asymmetric wide ASW. Non-corrosive mounting bracket allowing for adjustment angles between -140° to +185°. The luminaire is available in 2 sizes: M and L. Standard equipped with 0.1m long H07RN-F cable and IP66 quick connector. Wide range of accessories available: protective net, grip for the lighting pole, wall bracket.

APPLICATION

The fitting is dedicated for lighting elevations and billboards.


QUEST 2 LED M 21000LM I CL. IP66 730 SP10KV (184W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	696008	The number of implement units:	2
EAN:	5905963696008	Version:	M
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	321/424/37
Rated power of the luminaire [W]:	184	Impact resistance:	IK09
Supply voltage [V]:	220 - 240	Ingress protection:	IP66
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	21000	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	114	Lateral surface (SCx) [m2]:	0.140
Energy efficiency class:	E	Net weight [kg]:	4.200
Electrical protection class:	I	LED lifespan L70B50 [h]:	156000
Colour temperature [K]:	3000	LED lifespan L80B20 [h]:	98000
Colour rendering index:	70	LED lifespan L90B10 [h]:	47000
SDCM:	≤ 5	Cable length [m]:	0.25
Beam angle [°]:	120	Mark D:	yes
Surge protection [kV]:	10	Additional accessories:	protective grid, pole mount, wall mount
Diffuser material:	glass	Warranty [years]:	5
Diffuser type:	transparent	CE certificate:	86/2021
Optics material:	PC	PZH certificate:	B-BK-60212-0480/21
Optics:	lens	Environmental Product Declaration (EPD):	816/2025
Material of the body:	aluminium	Manual:	Download PDF
Colour of the body:	RAL 7016	Plik LDT:	Download

LIGHT CURVES



QUEST 2 LED M 21000LM I CL. IP66 730 SP10KV (184W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
559938	QUEST PLUS LED M/L wall holder RAL9006
699993	QUEST 2 LED M - recessed frame
699986	QUEST 2 LED L - recessed frame
699962	QUEST 2 LED L protective grid RAL7016
699979	QUEST 2 LED M protective grid RAL7016
965913	QUEST 2 LED M/L MAX wall mount RAL7016
567728	QUEST 2 LED M/L Pole holder



QUEST PLUS LED M/L wall holder
RAL9006 (559938)



QUEST 2 LED M - recessed
frame (699993)



QUEST 2 LED L - recessed
frame (699986)



QUEST 2 LED L protective grid
RAL7016 (699962)



QUEST 2 LED M protective grid
RAL7016 (699979)



QUEST 2 LED M/L MAX wall mount
RAL7016 (965913)



QUEST 2 LED M/L Pole
holder (567728)