EXPO ADJUST 1950LM ZOOM 22-55° BLACK 940 19W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	19
Luminous flux [lm]*:	1950
Colour temperature [K]:	4000
Diffuser material:	PC
Diffuser type:	transparent
Diffuser colour:	transparent
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	225/213/95
Warranty [years]:	5

CHARACTERISTICS

EXPO ADJUST are top quality aluminum projectors with LED COB light source. Mounted on a rail system, it increases the range of applications and allows the user to make rearrangement changes even after installation. The compact, small-sized aluminum body with a heat sink effectively dissipates excess heat from the projector and increases the life of the product. Expo Adjust projectors are friendly to people and the environment. They are innovative, highly energy-efficient projectors with excellent light efficiency and a minimalist, distinctive design.

APPLICATION

No emission of ultraviolet and infrared radiation and a high color rendering index (Ra <90), combined with the highest luminous efficiency and excellent product durability, allows the use of EXPO ADJUST wherever the highest quality of light is expected while maintaining energy efficiency. The main areas of application are accent lighting in commercial facilities, museums, exhibition halls, offices, and apartments.
The ZOOM version with adjustable lighting angle in the range of 22-55^0 increases the adaptive value of the product in the event of a change in the decor or the need for a different display of goods compared to the original assumptions.

EXPO ADJUST 1950LM ZOOM 22-55° BLACK 940 19W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	481383
EAN:	5905963481383
Light source:	COB
Nominal power [W]:	17.50
Rated power of the luminaire [W]:	19
Supply voltage [V]:	220 – 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	1950
Luminous efficacy [lm/W]:	103
Electrical protection class:	I
Colour temperature [K]:	4000
Color rendering index (Ra) >:	90
SDCM:	3
Beam angle [°]:	22-55
Diffuser material:	PC
Diffuser type:	transparent
Diffuser colour:	transparent

Optics material:	PC
Optics:	lens
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	225/213/95
Ingress protection:	IP20
Mounting version:	track
Working temperature [°C]:	from -20 to +25
Tilt angle adjustment [°]:	from 22 to 55
Energy efficiency class:	E
Net weight [kg]:	0.730
Light distribution type:	symmetric
Warranty [years]:	5
CE certificate:	214/2023
Manual:	Download PDF
ETIM class:	EC001744
Plik LDT:	Download

Card creation date: 10 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 214/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl