

EXPO ADJUST 2700LM ZOOM 22-55° BOX BLACK 940 30W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	30
Luminous flux [lm]*:	2700
Colour temperature [K]:	4000
Diffuser material:	PC
Diffuser type:	clear
Diffuser colour:	transparent
Material of the body:	aluminium. ABS box
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	225/213/95
Warranty [years]:	5

CHARACTERISTICS

EXPO ADJUST are top quality aluminum projectors with LED COB light source. The projectors are available in versions that allow mounting on rails, as well as surface and flush mounting, such as in plasterboard ceilings. Mounting on a trunking system, increases the range of applications and allows the user to make arrangement changes even after installation. The compact, small-sized aluminum body with a heat sink effectively dissipates excess heat from the projector and increases the life of the product. The aesthetically pleasing ABS box effectively masks the power supply housed in it. Expo Adjust projectors are friendly to people and the environment. They are innovative, highly energy-efficient projectors with excellent light efficiency and a minimalist, distinctive design.

APPLICATION

No emission of ultraviolet and infrared radiation and a high color rendering index (Ra >90), combined with the highest luminous efficiency and excellent product durability, allows the use of EXPO ADJUST wherever the highest quality of light is expected while maintaining energy efficiency. The main areas of application are accent lighting in commercial facilities, museums, exhibition halls, offices, and apartments.

The ZOOM version with adjustable lighting angle in the range of 22-55° increases the adaptive value of the product in the event of a change in the decor or the need for a different display of goods compared to the original assumptions.

EXPO ADJUST 2700LM ZOOM 22-55° BOX BLACK 940 30W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	481369	Diffuser type:	clear
Rated power of the luminaire [W]:	30	Diffuser colour:	transparent
EAN:	5905963481369	Optics material:	PC
Luminous flux [lm]:	2700	Optics:	lens
Light source:	COB	Tilt angle adjustment [°]:	yes; 22-55°
Colour temperature [K]:	4000	Dimensions (H/W/T/S) [mm]:	225/213/95
Nominal power [W]:	29	Ingress protection:	IP20
Colour rendering index:	>90	Working temperature [°C]:	from -20 to +25
Supply voltage [V]:	220 - 240	Energy efficiency class:	F
Mounting version:	track	Net weight [kg]:	0.730
Frequency [Hz]:	50 - 60	Light distribution type:	symmetric
Material of the body:	aluminium. ABS box	Warranty [years]:	5
Luminous efficacy [lm/W]:	90	CE certificate:	214/2023
Electrical protection class:	I	Manual:	Download PDF
Colour of the body:	black	ETIM class:	EC001744
SDCM:	≤ 3	Plik LDT:	
Beam angle [°]:	22-55		
Diffuser material:	PC		

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 214/2023