EXPO ADJUST 2350LM ZOOM 22-55° BLACK 930 30W

DETAILED CARD





TECHNICAL PARAMETERS

Rated power of the luminaire [W]*: 30

Luminous flux [lm]*: 2350

Colour temperature [K]: 3000

Diffuser material: PC

Diffuser type: transparent

Diffuser colour: transparent

Material of the body: aluminium

Colour of the body: black

Dimensions (H/W/T/S) [mm]: 225/213/95

Warranty [years]: 5

CHARACTERISTICS

EXPO ADJUST are top quality aluminum projectors with LED COB light source. Mounted on a rail system, it increases the range of applications and allows the user to make rearrangement changes even after installation. The compact, small-sized aluminum body with a heat sink effectively dissipates excess heat from the projector and increases the life of the product. Expo Adjust projectors are friendly to people and the environment. They are innovative, highly energy-efficient projectors with excellent light efficiency and a minimalist, distinctive design.

APPLICATION

No emission of ultraviolet and infrared radiation and a high color rendering index (Ra >90), combined with the highest luminous efficiency and excellent product durability, allows the use of EXPO ADJUST wherever the highest quality of light is expected while maintaining energy efficiency. The main areas of application are accent lighting in commercial facilities, museums, exhibition halls, offices, and apartments.

The ZOOM version with adjustable lighting angle in the range of $22-55^\circ$ increases the adaptive value of the product in the event of a change in the decor or the need for a different display of goods compared to the original assumptions.



EXPO ADJUST 2350LM ZOOM 22-55° BLACK 930 30W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	482090
EAN:	5905963482090
Light source:	СОВ
Nominal power [W]:	29
Rated power of the luminaire [W]:	30
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [Im]:	2350
Luminous efficacy [lm/W]:	79
Electrical protection class:	1
Colour temperature [K]:	3000
Color rendering index (Ra) >:	90
SDCM:	3
Beam angle [°]:	22-55
Diffuser material:	PC
Diffuser type:	transparent
Diffuser colour:	transparent
Optics material:	PC

Optics:	lens
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	225/213/95
Ingress protection:	IP20
Mounting version:	track
Working temperature [°C]:	from -20 to +25
Tilt angle adjustment [°]:	from 22 to 55
Energy efficiency class:	G
Net weight [kg]:	0.730
Light distribution type:	symmetric
Mounting dimensions [mm]:	225
Dimensions of bulk box (H/W/D) [mm]:	225/195/101
Warranty [years]:	5
CE certificate:	<u>214/2023</u>
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 10 July 2025



