

# EXPO ADJUST 3050LM DALI 36° BLACK 930 35W

DETAILED CARD



## TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	35
Luminous flux [lm]*:	3050
Colour temperature [K]:	3000
Diffuser material:	PC
Diffuser type:	transparent
Diffuser colour:	transparent
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	260/185/95
Warranty [years]:	5

## CHARACTERISTICS

EXPO ADJUST are top quality aluminum projectors with LED COB light source. The projectors are available in versions that allow mounting on rails, as well as surface and flush mounting, such as in plasterboard ceilings. Mounting on a trunking system, increases the range of applications and allows the user to make arrangement changes even after installation. The compact, small-sized aluminum body with a heat sink effectively dissipates excess heat from the projector and increases the life of the product. The aesthetically pleasing ABS box effectively masks the power supply housed in it. Expo Adjust projectors are friendly to people and the environment. They are innovative, highly energy-efficient projectors with excellent light efficiency and a minimalist, distinctive design.

## APPLICATION

No emission of ultraviolet and infrared radiation and a high color rendering index (Ra >90), combined with the highest luminous efficiency and excellent product durability, allows the use of EXPO ADJUST wherever the highest quality of light is expected while maintaining energy efficiency. The main areas of application are accent lighting in commercial facilities, museums, exhibition halls, offices, and apartments.

**The ZOOM version with adjustable lighting angle in the range of 22-55°** increases the adaptive value of the product in the event of a change in the decor or the need for a different display of goods compared to the original assumptions.

# EXPO ADJUST 3050LM DALI 36° BLACK 930 35W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	482298	Material of the body:	aluminium
EAN:	5905963482298	Colour of the body:	black
Light source:	COB	Dimensions (H/W/T/S) [mm]:	260/185/95
Nominal power [W]:	33.50	Ingress protection:	IP20
Rated power of the luminaire [W]:	35	Mounting version:	track
Supply voltage [V]:	220 – 240	Working temperature [°C]:	from -20 to +25
Frequency [Hz]:	50 - 60	Tilt angle adjustment [°]:	no; 36°
Luminous flux [lm]:	3050	Energy efficiency class:	G
Luminous efficacy [lm/W]:	89	DIMM DALI:	yes
Electrical protection class:	II	Control:	DALI
Colour temperature [K]:	3000	Net weight [kg]:	0.660
Colour rendering index:	90	Light distribution type:	symmetric
SDCM:	≤ 3	Mounting dimensions [mm]:	260
Beam angle [°]:	36	Dimensions of bulk box (H/W/D) [mm]:	260/260/87
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	transparent	CE certificate:	<a href="#">214/2023</a>
Diffuser colour:	transparent	Manual:	<a href="#">Download PDF</a>
Optics material:	PC	Plik LDT:	<a href="#">Download</a>
Optics:	lens		