

BARIS 40 LED Z 2100LM PLX DALI I CL. IP20 860MM 830 23W ANODE CO

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|-----------|
| Index: | 931024 |
| Rated power of the luminaire [W]*: | 23 |
| Luminous flux [lm]*: | 2100 |
| Colour temperature [K]: | 3000 |
| Ingress protection: | IP20 |
| Energy efficiency class: | E |
| Material of the body: | aluminium |
| Colour of the body: | grey |
| Diffuser material: | PC |
| Diffuser type: | OPAL |

CHARACTERISTICS

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). The optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires to have 1.2m long slings in a set with a box.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms. Wall lamps are intended, among others for use in corridors, passageways as well as sanitary rooms and bathrooms, where IP44 class is required

BARIS 40 LED Z 2100LM PLX DALI I CL. IP20 860MM 830 23W ANODE CO

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------|----------------------------------|---|
| Index: | 931024 | DIMM DALI: | 1 |
| EAN: | 5905963931024 | Mounting version: | suspended |
| Light source: | LED | Net weight [kg]: | 1.100 |
| Rated power of the luminaire [W]: | 23 | Category type: | battens |
| Colour temperature [K]: | 3000 | AC voltage range [V]: | 198 - 264 |
| Luminous flux [lm]: | 2100 | LED lifespan L70B50 [h]: | 111500 |
| Nominal power [W]: | 22 | LED lifespan L80B20 [h]: | 70400 |
| Diffuser type: | OPAL | LED lifespan L90B10 [h]: | 34000 |
| Frequency [Hz]: | 50 - 60 | Product line: | 860 |
| Luminous efficacy [lm/W]: | 97 | Supply voltage [V]: | 220 - 240 |
| Energy efficiency class: | E | Optics: | no |
| Electrical protection class: | I | Impact resistance: | IK03 |
| Colour rendering index: | >80 | Working temperature [°C]: | from -25 to +35 |
| SDCM: | ≤ 3 | Control: | DALI |
| Power factor: | 0.85 | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Diffuser material: | PC | CE certificate: | 237/2023 |
| Diffuser colour: | milky | ENEC Certificate: | PL BBJ/003/2022/M1/A1 |
| Colour of the body: | grey | PZH certificate: | |
| Material of the body: | aluminium | Warranty [years]: | 5 |
| Dimensions (H/W/T/S) [mm]: | 53/40/860 | Manual: | Download PDF |
| Ingress protection: | IP20 | Plik LDT: | Pobierz |
| Mounting dimensions [mm]: | 720 | | |

Card creation date: 08 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 237/2023