


# BARIS 40 LED Z 2500LM PRM DALI I CL. IP20 860MM 840 23W BLACK

## DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	930379
<b>Rated power of the luminaire [W]*:</b>	23
<b>Luminous flux [lm]*:</b>	2500
<b>Colour temperature [K]:</b>	4000
<b>Ingress protection:</b>	IP20
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	black
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	PRM

## CHARACTERISTICS

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). The optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires to have 1.2m long slings in a set with a box.

## APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms. Wall lamps are intended, among others for use in corridors, passageways as well as sanitary rooms and bathrooms, where IP44 class is required


# BARIS 40 LED Z 2500LM PRM DALI I CL. IP20 860MM 840 23W BLACK

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	930379	Net weight [kg]:	1.100
EAN:	5905963930379	Category type:	luminaires and linear systems
Light source:	LED	AC voltage range [V]:	198 - 264
Rated power of the luminaire [W]:	23	LED lifespan L70B50 [h]:	111500
Nominal power [W]:	22	LED lifespan L80B20 [h]:	70400
Frequency [Hz]:	50 - 60	LED lifespan L90B10 [h]:	34000
Luminous flux [lm]:	2500	Product line:	860
Luminous efficacy [lm/W]:	109	DIMM DALI:	yes
Energy efficiency class:	D	Supply voltage [V]:	220 - 240
Electrical protection class:	I	Optics:	Microprism
Colour temperature [K]:	4000	Impact resistance:	IK06
Color rendering index (Ra) >:	80	Working temperature [°C]:	from -25 to +35
SDCM:	3	Control:	DALI
Power factor:	0.85	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	PRM	CE certificate:	<a href="#">237/2023</a>
Diffuser colour:	transparent	ENEC Certificate:	<a href="#">PL BBJ/003/2022/M1/A1</a>
Material of the body:	aluminium	PZH certificate:	
Colour of the body:	black	Manual:	<a href="#">Download PDF</a>
Dimensions (H/W/T/S) [mm]:	53/40/860	Environmental Product Declaration (EPD):	<a href="#">852/2025</a>
Mounting dimensions [mm]:	720	Category of application:	office lighting
Ingress protection:	IP20	Plik LDT:	<a href="#">Download</a>
Mounting version:	suspended		

### LIGHT CURVES



Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 237/2023