

BARIS 40 LED BRACKET 1500LM PRM I CL. IP44 860MM 830 13W ANODE CO

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	13
Luminous flux [lm]*:	1500
Colour temperature [K]:	3000
Ingress protection:	IP44
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	PRM
Mounting version:	surface, wall mounted

CHARACTERISTICS

A luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). Optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy.

APPLICATION

The unique design predisposes these luminaires to illuminate: offices, conference rooms, and other representative spaces, in offices, passageways, sanitary rooms, and bathrooms (wall lamps), in public utility buildings.

Versions marked "VD" are only intended for use in traffic zones and corridors inside buildings included in Table 5.1 of EN12464.

BARIS 40 LED BRACKET 1500LM PRM I CL. IP44 860MM 830 13W ANODE CO

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	674020	Ingress protection:	IP44
EAN:	5905963674020	Mounting version:	surface, wall mounted
Light source:	LED	Dimensions of single box [mm]:	1220/120/93
Rated power of the luminaire [W]:	13	Number on the palette [pcs]:	72
Nominal power [W]:	13	Net weight [kg]:	1
Frequency [Hz]:	50 - 60	Category type:	battens
Luminous flux [lm]:	1500	AC voltage range [V]:	198 - 264
Luminous efficacy [lm/W]:	110	LED lifespan L70B50 [h]:	111500
Energy efficiency class:	E	LED lifespan L80B20 [h]:	70400
Electrical protection class:	I	LED lifespan L90B10 [h]:	34000
Colour temperature [K]:	3000	Supply voltage [V]:	220 - 240
Colour rendering index:	>80	Optics:	Microprism
SDCM:	≤ 3	Impact resistance:	IK03
Diffuser material:	PC	Working temperature [°C]:	from -25 to +35
Diffuser type:	PRM	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser colour:	clear	Warranty [years]:	5
Material of the body:	aluminium	CE certificate:	240/2023
Colour of the body:	grey	ENEC Certificate:	PL BBJ/012/2021/M1/A1
Dimensions (H/W/T/S) [mm]:	53/71/860	PZH certificate:	
Mounting dimensions [mm]:	165	Manual:	Download PDF

LIGHT CURVES



Card creation date: 08 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 240/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl