

# BARIS 40 LED BRACKET 4150LM PRM DALI I CL. IP44

## 860MM 830 39W WHITE

DETAILED CARD



### TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	39
Luminous flux [lm]*:	4150
Colour temperature [K]:	3000
Ingress protection:	IP44
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	PRM
Mounting version:	surface, wall mounted

### CHARACTERISTICS

A luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). Optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy.

### APPLICATION

The unique design predisposes these luminaires to illuminate: offices, conference rooms, and other representative spaces, in offices, passageways, sanitary rooms, and bathrooms (wall lamps), in public utility buildings. Versions marked "VD" are only intended for use in traffic zones and corridors inside buildings included in Table 5.1 of EN12464.

# BARIS 40 LED BRACKET 4150LM PRM DALI I CL. IP44


## 860MM 830 39W WHITE

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	675232	DIMM DALI:	yes
EAN:	5905963675232	Dimensions of single box [mm]:	1220/120/93
Light source:	LED	Number on the palette [pcs]:	72
Rated power of the luminaire [W]:	39	Net weight [kg]:	1.100
Nominal power [W]:	38	Category type:	luminaires and linear systems
Frequency [Hz]:	50 - 60	AC voltage range [V]:	198 - 264
Luminous flux [lm]:	4150	LED lifespan L70B50 [h]:	111500
Luminous efficacy [lm/W]:	111	LED lifespan L80B20 [h]:	70400
Energy efficiency class:	E	LED lifespan L90B10 [h]:	34000
Electrical protection class:	I	Supply voltage [V]:	220 - 240
Colour temperature [K]:	3000	Optics:	Microprism
Colour rendering index:	80	Impact resistance:	IK06
SDCM:	≤ 3	Working temperature [°C]:	from -25 to +35
Diffuser material:	PC	Control:	DALI
Diffuser type:	PRM	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser colour:	transparent	Warranty [years]:	5
Material of the body:	aluminium	CE certificate:	<a href="#">240/2023</a>
Colour of the body:	white	ENEC Certificate:	<a href="#">PL BBJ/012/2021/M1/A1</a>
Dimensions (H/W/T/S) [mm]:	53/71/860	PZH certificate:	
Mounting dimensions [mm]:	165	Manual:	<a href="#">Download PDF</a>
Ingress protection:	IP44	Plik LDT:	<a href="#">Download</a>
Mounting version:	surface, wall mounted		

### LIGHT CURVES



Card creation date: 03 January 2025  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

This product is a subject to electric and electronic waste equipment regulations (WEEE).

Certificate CE - Nr: 240/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)