

# BARIS LED KINKIET 5325LM PRM DALI I CL. IP44 860MM 830 39W BLACK

## DETAILED CARD



### TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	39
Luminous flux [lm]*:	5325
Colour temperature [K]:	3000
Ingress protection:	IP44
Energy efficiency class:	C
Material of the body:	aluminium
Colour of the body:	black
Diffuser material:	PC
Diffuser type:	PRM
Mounting version:	surface, wall mounted

### CHARACTERISTICS

A luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). Optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy.

### APPLICATION

The unique design predisposes these luminaires to illuminate: offices, conference rooms, and other representative spaces, in offices, passageways, sanitary rooms, and bathrooms (wall lamps), in public utility buildings.

Versions marked "VD" are only intended for use in traffic zones and corridors inside buildings included in Table 5.1 of EN12464.


# BARIS LED KINKIET 5325LM PRM DALI I CL. IP44 860MM 830 39W BLACK

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	674877	Number on the palette [pcs]:	72
EAN:	5905963674877	Net weight [kg]:	1.100
Light source:	LED	Category type:	luminaires and linear systems
Rated power of the luminaire [W]:	39	AC voltage range [V]:	198 - 264
Nominal power [W]:	38	LED lifespan L70B50 [h]:	150000
Frequency [Hz]:	50 - 60	LED lifespan L80B20 [h]:	100000
Luminous flux [lm]:	5325	LED lifespan L90B10 [h]:	50000
Luminous efficacy [lm/W]:	137	DIMM DALI:	yes
Energy efficiency class:	C	Supply voltage [V]:	220 - 240
Electrical protection class:	I	Optics:	Microprism
Colour temperature [K]:	3000	Impact resistance:	IK06
Color rendering index (Ra) >:	80	Working temperature [°C]:	from -25 to +35
SDCM:	3	Control:	DALI
Diffuser material:	PC	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser type:	PRM	Warranty [years]:	5
Diffuser colour:	transparent	CE certificate:	<a href="#">240/2023</a>
Material of the body:	aluminium	ENEC Certificate:	<a href="#">PL BBJ/012/2021/M1/A1</a>
Colour of the body:	black	PZH certificate:	<a href="#">Download PDF</a>
Dimensions (H/W/T/S) [mm]:	53/71/860	Environmental Product Declaration (EPD):	<a href="#">852/2025</a>
Mounting dimensions [mm]:	165	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Ingress protection:	IP44	Plik LDT:	<a href="#">Download</a>
Mounting version:	surface, wall mounted		
Dimensions of single box [mm]:	1220/120/93		

### LIGHT CURVES



Card creation date: 17 February 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).  Certificate CE - Nr: 240/2023