

BARIS 52 LED BRACKET 860MM 1300LM 830 IP44 I CL. PLX ANODE CO 13W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|-----------------------|
| Rated power [W] - range: | 13 |
| Luminous flux of the luminaire [lm] - range: | 1300 |
| Colour temperature [K]: | 3000 |
| Ingress protection: | IP44 |
| Impact resistance: | IK03 |
| Material of the body: | aluminium |
| Colour of the body: | grey |
| Diffuser material: | PC |
| Diffuser type: | OPAL |
| Mounting version: | surface, wall mounted |

CHARACTERISTICS

Discreet elegance and energy efficiency are the special features of the BARIS 52 LED Bracket lamp family. The housing of the luminaire is made of an anodized aluminum profile in gray or an aluminum profile painted in white or black (other colors available on request). The supplement is a spacer made of plastic. The optical system is crowned with an opal diffuser providing soft light. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmission than the opal cover, which has a direct impact on a higher value of luminous efficacy. The available DIR / IND versions provide up / down two-way light distribution in the proportions 65/35.

APPLICATION

A unique design predisposes these luminaires to be illuminated: passageways, sanitary rooms, and bathrooms, as well as living rooms and hotel rooms.

The Baris 52 Bracket luminaires perfectly display light paintings, posters or other works hung on the walls.

BARIS 52 LED BRACKET 860MM 1300LM 830 IP44 I CL. PLX ANODE CO 13W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------|----------------------------|--------------------------------------|
| Index: | 455896 | Diffuser material: | PC |
| EAN: | 5905963455896 | Diffuser type: | OPAL |
| Light source: | LED module | Diffuser colour: | milky |
| Rated power [W] - range: | 13 | Optics: | no |
| Nominal power [W] - range: | 13 | Material of the body: | aluminium |
| Luminous flux of the luminaire [lm] - range: | 1300 | Colour of the body: | grey |
| Supply voltage [V]: | 220 - 240 | Dimensions (H/W/T/S) [mm]: | 82/69/864 |
| Frequency [Hz]: | 50 - 60 | Impact resistance: | IK03 |
| Luminous efficacy [lm/W]: | 95 | Ingress protection: | IP44 |
| Energy efficiency class: | E | Mounting version: | surface, wall mounted |
| Electrical protection class: | I | Working temperature [°C]: | from -25 to +35 |
| Colour temperature [K]: | 3000 | Net weight [kg]: | 1.500 |
| Colour rendering index: | >80 | Warranty [years]: | 5 |
| SDCM: | ≤ 3 | CE certificate: | 228/2023 |
| LED lifespan L70B50 [h]: | 111500 | ENEC Certificate: | PL BBJ/006/2022/M1 |
| LED lifespan L80B20 [h]: | 70400 | PZH certificate: | B-BK-60112-0357/2023 |
| LED lifespan L90B10 [h]: | 34000 | Manual: | Download PDF |

LIGHT CURVES



Card creation date: 11 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 228/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl