

TERRA 2 LED LONG N-MAG X2 1195X140MM 4200LM 840 WHITE GLOSS (36W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	990038
Ingress protection:	IP20
Nominal power [W]:	36
Luminous flux [lm]*:	4200
Colour rendering index:	>80
SDCM:	≤ 3
Material of the body:	powder coated steel
Mounting version:	surface (magnet ver.)
Dimensions (H/W/T/S) [mm]:	1195/140/36

CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter) or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

TERRA 2 LED LONG N-MAG X2 1195X140MM 4200LM 840 WHITE GLOSS (36W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	990038	Colour of the body:	white gloss
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	1195/140/36
Nominal power [W]:	36	Ingress protection:	IP20
Rated power of the luminaire [W]:	40	Mounting version:	surface (magnet ver.)
Supply voltage [V]:	220 - 240	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	4200	Category type:	louvres
Luminous efficacy [lm/W]:	106	Category of application:	commercial facilities, educational institutions
Energy efficiency class:	E	Version:	2x1
Electrical protection class:	II	AC voltage range [V]:	220 - 240
Colour temperature [K]:	4000	UGR (4H8H):	< 16.7
Colour rendering index:	>80	LED lifespan L70B50 [h]:	132000
SDCM:	≤ 3	LED lifespan L80B20 [h]:	84000
Power factor:	0.96	LED lifespan L90B10 [h]:	42000
Optics:	HE	CE certificate:	354/2023
Material of the body:	powder coated steel	Manual:	Download PDF

Card creation date: 31 August 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 354/2023