

TERRA 2 LED N-MAG 595X300MM X2 2400LM 830 WHITE MAT (20W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	990502
Ingress protection:	IP20
Nominal power [W]:	20
Luminous flux [lm]*:	2400
Colour rendering index:	>80
SDCM:	≤ 3
Material of the body:	powder coated steel
Mounting version:	surface (magnet ver.)
Dimensions (H/W/T/S) [mm]:	595/300/36

CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter) or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

TERRA 2 LED N-MAG 595X300MM X2 2400LM 830 WHITE MAT (20W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	20	Electrical protection class:	II
Index:	990502	Colour rendering index:	>80
Colour temperature [K]:	3000	SDCM:	≤ 3
Light source:	LED module	Power factor:	0.95
Luminous flux [lm]:	2400	Material of the body:	powder coated steel
Optics:	HE	Ingress protection:	IP20
Rated power of the luminaire [W]:	22.70	Working temperature [°C]:	from -20 to +35
Version:	2x1	Category type:	louvres
Supply voltage [V]:	220 - 240	Category of application:	commercial facilities, educational institutions
Colour of the body:	white mat	LED lifespan L70B50 [h]:	132000
Frequency [Hz]:	50 - 60	LED lifespan L80B20 [h]:	84000
Dimensions (H/W/T/S) [mm]:	595/300/36	LED lifespan L90B10 [h]:	42000
Mounting version:	surface (magnet ver.)	CE certificate:	354/2023
Luminous efficacy [lm/W]:	106	Manual:	Download PDF
Energy efficiency class:	E		

Card creation date: 03 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 354/2023