OCULUS LED DALI 34650LM 857 IP66 I CL. 75D SP10KV 206W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	977206
Nominal power [W]:	206
Luminous flux [lm]*:	34650
Colour temperature [K]:	5700
Electrical protection class:	I
Energy efficiency class:	B
Material of the body:	powder coated aluminium
Diffuser material:	PC
Beam angle [°]:	75
Working temperature [°C]:	from -25 to +45

CHARACTERISTICS

OCULUS LED is a HIGH-BAY luminaire from the NEXT GEN product line, constituting a new generation of luminaires dedicated to LED technology. The designed-from-scratch body – made of die-cast aluminium and powder coated – uses natural conduction and convection processes, which have a positive effect on luminaire's heat management. The shape of the body with an integrated, effective heat sink and high-quality materials ensure maximum heat dissipation from the LED module. The driver's external compartment, separated from the body, guarantees optimal thermal working conditions for the power supply system. This enables the luminaire to work in an ambient temperature of max 60°C. LEDs from a reputable manufacturer and new LED modules enable very high luminous efficiency: max 176 lm/W. This guarantees that the required lighting level and significant energy savings are achieved. The diffuser and optical system are composed of precise linear lenses made of polycarbonate (PC). There are 3 dedicated ranges of light distribution available: 55°, 75°, 105°. GLASS version with tempered glass (without lenses) and 105° distribution is also available.
Standard equipped with a 0.3 m long H07RN-F cable terminated with an additional male and female connector, which makes the assembly easier and more convenient.
Available version with radio motion sensor:
- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).
Its design is adapted for suspended mounting and surface mounting (ceiling and wall) requiring the use of additional accessories.

APPLICATION

The luminaire is intended for suspended mounting (using chains, wires, etc.) both indoors and outdoors. It will prove perfect for manufacturing plants and halls as well as large-format warehouses and logistics centres.


OCULUS LED DALI 34650LM 857 IP66 I CL. 75D SP10KV 206W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	977206	**Impact resistance:**	IK09
EAN:	5905963977206	**Ingress protection:**	IP66
Light source:	LED module	**Mounting version:**	suspended
Nominal power [W]:	206	**Working temperature [°C]:**	from -25 to +45
Rated power of the luminaire [W]:	216.80	**DIMM DALI:**	yes
Supply voltage [V]:	220-240	**The number of implement units:**	2
Frequency [Hz]:	50-60	**Cable length [m]:**	0.30
Luminous flux [lm]:	34650	**Dimensions of single box [mm]:**	135/372/372
Luminous efficacy [lm/W]:	160	**Net weight [kg]:**	3.680
Energy efficiency class:	B	**Category type:**	high-bay and low-bay
Electrical protection class:	I	**AC voltage range [V]:**	198 - 264
Colour temperature [K]:	5700	**DC voltage range [V]:**	176 - 280
Color rendering index (Ra) >:	80	**LED lifespan L70B50 [h]:**	196000
SDCM:	3	**LED lifespan L80B10 [h]:**	123000
Power factor:	0.98	**LED lifespan L90B10 [h]:**	60000
Beam angle [°]:	75	**Warranty [years]:**	5
Surge protection [kV]:	4	**ENEC Certificate:**	PL BBJ/005/2021/M1
Diffuser material:	PC	**CE certificate:**	153/2023
Diffuser colour:	transparent	**PZH certificate:**	B-BK-60212-0481/21
Optics material:	PC	**HACCP:**	852/2004
Optics:	lens	**Environmental Product Declaration (EPD):**	816/2025
Material of the body:	powder coated aluminium	**Manual:**	Download PDF
Colour of the body:	grey	**Plik LDT:**	Download
Dimensions (H/W/T/S) [mm]:	125/371		

LIGHT CURVES



OCULUS LED DALI 34650LM 857 IP66 I CL. 75D SP10KV 206W


DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
964244	OCULUS LED - RCR motion sensor
964886	OCULUS LED - universal handle-lack of compatibility with Dali version 294W
964893	OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W
964862	OCULUS LED - protective grid
963674	OCULUS LED - RCR / PIR DALI motion sensor
WSEL438	Remote control for motion sensor HD01R
WSEL415	WSEL415 Remote control for - PIR sensor




OCULUS LED - RCR motion sensor (964244)



OCULUS LED - universal handle-lack of compatibility with Dali version 294W (964886)




OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W (964893)




OCULUS LED - protective grid (964862)



OCULUS LED - RCR / PIR DALI motion sensor (963674)



Remote control for motion sensor HD01R (WSEL438)



WSEL415 Remote control for - PIR sensor (WSEL415)

Card creation date: 10 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 153/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl