


INDUSTRY SLIM LED 590MM 4550LM 840 IP66 120D LS2 (28W)

DETAILED CARD



INDUSTRY SLIM LED 590MM 4550LM 840 IP66 120D LS2 (28W)

DETAILED CARD

TECHNICAL PARAMETERS

Ingress protection:	IP66
Rated power of the luminaire [W]*:	28
Luminous flux [lm]*:	4550
Colour temperature [K]:	4000
Material of the body:	aluminium
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	transparent
Mounting version:	surface, suspended

CHARACTERISTICS

Industry Slim Led - a brand new industrial luminaire is characterized by high luminous flux and very high luminous efficiency >160 lm/W, which makes this luminaire highly energy-efficient and environmentally friendly. It is distinguished by its very high IP66 tightness. It owes this tightness to its well-thought-out design. The polycarbonate diffuser is permanently attached to the housing with a durable silicone gasket. This means that in addition to the tightness thus achieved, the light module is protected from uncontrolled interference and access to the LEDs. The tightness of the lamp, is ensured by the gland, which screwed tightens the gasket and prevents the penetration of dust or moisture and water. Industry Slim Led allows for pendant or surface mounting.

APPLICATION

The luminaire is designed to illuminate industrial and warehouse facilities, due to its minimal dimensions, also in hard-to-reach places. The Industry Slim Led luminaire is available in various versions: with different optics, wide, narrow, and dedicated to high-bay light distribution, and five types of the diffuser, including an anti-glare diffuser.

DETAILS




INDUSTRY SLIM LED 590MM 4550LM 840 IP66 120D LS2 (28W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	934308	Material of the body:	aluminium
EAN:	5905963934308	Colour of the body:	grey
Rated power of the luminaire [W]:	28	Dimensions (H/W/T/S) [mm]:	651/50/75
Luminous flux [lm]:	4550	Ingress protection:	IP66
Supply voltage [V]:	220 - 240	Impact resistance:	IK09
Frequency [Hz]:	50 - 60	Mounting version:	surface, suspended
Luminous efficacy [lm/W]:	163	Working temperature [°C]:	from -25 to +35
Energy efficiency class:	B	Wire type:	5x1,5
Electrical protection class:	I	Through wiring:	LS2
Colour temperature [K]:	4000	Net weight [kg]:	1.300
Color rendering index (Ra) >:	80	Light distribution type:	symmetric
SDCM:	3	Warranty [years]:	5
LED lifespan L70B50 [h]:	179000	CE certificate:	167/2023
LED lifespan L80B10 [h]:	113000 (Ta 25°C)	ENEC Certificate:	0362/ENEC/24
LED lifespan L90B10 [h]:	54000	Manual:	Download PDF
Beam angle [°]:	120	Environmental Product Declaration (EPD):	852/2025
Diffuser material:	PC	Pliik LDT:	Download

LIGHT CURVES



INDUSTRY SLIM LED 590MM 4550LM 840 IP66 120D LS2 (28W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
60000006	M16 stuffing box plug various PA black M-16 - BPM-21



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 167/2023